







Produktfamilj
Miller Rope/Web Lanyards
(EUR)









A restraint lanyard is used to restrict the worker's movement to prevent him reaching a location where a fall hazard exists.



Product Numbers &

	1002881	MD00 Rope Lanyard 1m with loop and connector (ML00), 18mm opening
	1002882	MD00 Rope Lanyard 2m with loop and connector (ML00), 18mm opening
	1002883	MD02 Rope Lanyard 1m with two connectors (ML00), 18mm opening
	1002884	MD02 Rope Lanyard 2m with two connectors (ML00), 18mm opening
	1002885	Lanyard 1m, 12mm, with ML00 + ML04
	1002886	Lanyard 2m, 12mm, with ML00 + ML04

Miller Rope-Web Lanyards (EUR)

	1002887	MD06 Forked rope lanyard 0,35m - for attachment to harness front anchorage D-rings : confined space access, rescue or attachment to a ladder
	1002889	Back anchorage Extended web back anchorage 0.3m
	1002890	Web lanyard 0.17m, with ML00, for MG00
	1003135	Rope connection lanyard 1m
	1003137	Connection lanyard 1,5m
	1004711	MD02 Rope Lanyard 1,5m with two connectors (ML00), 18mm opening
	1004576	LANYARD, ROPE 12mm, SCAF.HOOK, 2m
	1015859	ATEX Forked Lanyard Forked Lanyard

Översikt

Viktigaste egenskaperna

Miller has a comprehensive range of lightweight, versatile restraint arrest lanyards designed for maximum protection.

Rekommenderade branscher/rekommenderat användningsområde

- Byggindustri
- Tillverkning
- Vatten och energi

Risker

- Fall från höga höjder

Föreskrifter

- EN 354 -

Garantiinformation

Our state of the art equipment provides the critical tool for worker protection, combining mobility with unsurpassed comfort.

At our ISO 9001 certified manufacturing facilities in Europe, we ensure that every Miller product is made in accordance with the standards and meets your exacting requirements.

Trycksaker & dokument

90004208 lanyard EN 354, 355 (EUR)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards/41642/1033.aspx

Instruction manual

Teknisk support

Miller Techniserv

Phone: +49 (0) 9281/8302-205

Email: techniservnorth.hsp@honeywell.com