



Produktfamilj

MC91A

MC91A are constant flow supplied air respirators designed to EN14594. A regulator in the waistbelt unit maintains an constant adustable flow into the mask ensuring that no contamination can enter. P3 safety filter ensures protection continuation against particles when disconnecting the air network. For asbestos removal operations.



Product Numbers &



1762920

MC91A regulator, hose, RBE06 belt



1762921

MC91A regulator, hose, AQR06 belt



1762992

MC91A Supplied Air belt for asbestos with full-face mask

MC 91A supplied air belt with Cosmo full-face mask in EPDM, P3 filter with double threading, 10 m hose in a carrying box - for asbetos applications



1762995

MC91A Supplied Air belt for asbestos with full-face mask

MC 91A supplied air belt with Cosmo full-face mask in silicone, P3 filter with double threading, 10 m hose in a carrying box - for asbetos applications



1760203

Regulator MC91A, CEJN

Översikt

Viktigaste egenskaperna

P3 filter with double threading for continued protection when disconnecting the air network.
Flow 120 l/min to 300 l/min.

Risker

- Luftburna partiklar

Föreskrifter

- EN14594 - Respiratory protective devices - Continuous flow compressed air line breathing apparatus

Specifikationer

Maximum flow rate

- 300 l/min

Minimum flow rate

- 120l/min

Connections

- AQR06 or RBE6

Head piece

- Full-face masks

NPF

- 2000

APF

- 40

Trycksaker & dokument

NU020-06 MC91A SPERIAN CE 10L _1771892

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Respiratory_Protection/4294983645/1033.aspx

Training & Proper Use

Refer to user manual