



Product Family
Miller Revolution Premium R5
Harnesses (EUR)

3-point full body harness for use with a fall arrest device and suitable anchorage point. The robust Miller Revolution harness is ideal for scaffolding, steel erection, tower building and maintenance thanks to the unique Revolution technology and a multitude of key features.

Miller Logo

Product Numbers & Ordering Information

	Product Numbers	Details
	1014251	R5 Revolution Premium Duraflex S/M 3-point, DuraFlex Webbing, with quick-fixing buckles, rotating work-positioning belt, size S/M
	1014252	R5 Revolution Premium Duraflex L/XL 3-point, DuraFlex Webbing, with quick-fixing buckles, rotating work-positioning belt, size L/XL
	1014253	R5 Revolution Premium Duraflex XXL 3-point, DuraFlex Webbing, with quick-fixing buckles, rotating work-positioning belt, size XXL
	1014254	R5 Revolution Premium DualTech S/M 3-point, DualTech Webbing, with quick-fixing buckles, rotating work-positioning belt, size S/M
	1014255	R5 Revolution Premium DualTech L/XL 3-point, DualTech Webbing, with quick-fixing buckles, rotating work-positioning belt, size L/XL
	1014256	R5 Revolution Premium DualTech XXL 3-point, DualTech Webbing, with quick-fixing buckles, rotating work-positioning belt, size XXL

Overview

Key Features

Features:

This Revolution R5 premium 3 pts Harness is perfect for utilities & telecom. Engineered with pivot link connexion on the hips and automatic webbing adjustment for a more comfortable fit and a great freedom of movement. Equipped with automatic buckles and Ergo Armor back shield & work positioning belt. This rotating work positioning belt offers a more comfortable fit and a greater mobility. Webbing on the Padded legs straps are sliding, and provide a perfect easy-to-fit.

Benefits:

PivotLink Connection (patented): This unique rotary design provides greater comfort in bending / mobility. Positioned at waist level to mirror the bending and squatting movements of the worker in construction and maintenance. Provides attachment point for tools and accessories. Made of stainless steel for corrosion resistance. In the event of a fall the PivotLink improves the harness resistance due to an improved distribution of the efforts.

ErgoArmor Back Shield: This semi-flexible back shield minimizes impact from sharp / heavy snap hooks and self retracting lifelines. The self-adjusting channels conform to a variety of body shapes. The padding conforms to unlimited back contours while allowing superior air flow. A knitted mesh membrane minimizes moisture absorption and maintains an optimal air circulation whilst also helping to position the back D-ring correctly.

Self Contained Label Pack (patented): encapsulates labels minimizing damage and loss. Durable, polymer construction for extended service life. Integrated and oversized pull-free lanyard rings. Protection against light, rain, abrasion and dust.

Cam Buckle (patented): Easy, one-hand adjustment / release allows simultaneous adjustment of shoulder straps. Promotes proper snug fit; will not slip or misadjust. Constructed of high-tech polymer, lightweight aluminium and stainless steel materials that resist rust/corrosion.

Web Finials (patented): Clip-on design safely organises webbing after proper adjustment. Constructed of durable, high-impact resistant polymer. Provides positive gripping surface for easy web adjustment.

DualTech Webbing (patented): Donning made easy with two-sided, contrasting colour webbing and textures: soft grey polyamide webbing on the inside and durable, abrasion resistant polyester webbing on the outside. Webbing engineered with shape retention memory for a more comfortable fit. Unique circular tack provides greater strength, and contrasting colours make inspection easier.

DuraFlex® Webbing : Patented, elastomer webbing specially formulated to stretch with the user's movements so there is no bunching or binding.

Work positioning belt for a more comfortable hands-free position when used in conjunction with a positioning lanyard.

Custom Identification: Four brightly coloured permanent labels allow customisation for date of service, specific trade, sub-contractor etc. A write in window allows space for individual names or other information.

Recommended Industries/Use

- Utilities

Hazards

- Fall from height

Regulations

- EN 361 & 358 - All Miller harnesses are CE certified and comply with EN 361 and, where necessary, with EN 358

Warranty Information

Our state of the art equipment provides the critical tool for worker protection, combining mobility with unsurpassed comfort.

At our ISO 9001 certified manufacturing facilities in Europe, we ensure that every Miller product is made in accordance with the standards and meets your exacting requirements.

Literature & Documents

Miller Revolution Instruction manual - 90014448 (EUR)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Full_Body_Harness/40873/1033.aspx

Instruction manual

90004212 harness EN 361, 358 (EUR)

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Full_Body_Harness/41640/1033.aspx

Instruction manual

Training & Proper Use

Training is an essential part of any safety program. The employer is responsible for ensuring that any person working at height is fully informed regarding the correct use of PPE and systems.

More information about the training...

Technical Support

Miller Techniserv

Northern and Central Europe

Phone: +49 (0) 9281/8302-205

Email: techniservnorth.hsp@honeywell.com

Southern Europe, UK, Ireland

Phone: +33 (0)2 48 52 40 42

Email: techniserv.hsp@honeywell.com

