


Product Family
Rope Grab non-removable
RG-300 Titan2

Smooth sliding vertical fall arrest system that will provide greater safety & comfort at work to quickly access the work site and better focus on their job to improve their productivity



Product Numbers & Ordering Information

	Product Numbers	Details
	1035931	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 5M
	1035932	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 10M
	1035933	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 15M
	1035934	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 20M
	1035935	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 25M
	1035936	RG non-removable RG300 RG300 Automatic Rope Grab Ø11mm W/Anchorage 30M



1035937

RG non-removable RG300
RG300 Automatic Rope Grab Ø11mm W/Anchorage 40M



1035938

RG non-removable RG300
RG300 Automatic Rope Grab Ø11mmW/ Anchorage 50M

Overview

Recommended Industries/Use

- Construction
- Utilities

Hazards

- Fall from height

Regulations

- EN353-2:2002 - CNB/P/11.075

Historical Brand

Honeywell Miller

Specifications

A product that suits all work situations

- Product tested on edges with an angle radius ≥ 0.5 mm. Tested at 140kg in all situations at height

Comfort and freedom of movement

- Easy to manipulate, intuitive product

Better security

- Increased Security

Reliability

- Corrosion resistant stainless steel construction provides increased durability

Literature & Documents

Honeywell Miller Rope Grab- RG500 _300 Brochure

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/4295003784/1033.aspx

DELIVERING SECURITY AT NEW HEIGHTS Rope Grabs Prevent Work Site Falls FEATURES AND BENEFITS • Compliant to EN 353-2:2002 • Maximum user weight of 140 kg • Long-lasting product in standard conditions • Can be used as anchorage device (EN 795/B:2012) 18 kN • Resistant to shocks and dust • Slides smoothly on the rope (vertical)