








Product Family
ARACUT® SLEEVES

Knitted Kevlar® sleeves. Forearm protection. Cut resistant (Level 3 to EN 388) and heat resistant (contact heat).



Product Numbers & Ordering Information

	Product Numbers	Details
	4150064	ARACUT® SLEEVES 14. 2 ply Kevlar® knitted sleeve. Thumbhole. Length : 35 cm. (Unique size)
	4150055	ARACUT® SLEEVE II 2 ply Kevlar® knitted sleeve. Thumbhole. Split cowhide leather reinforcement. Length : 36 cm. (Unique size)
	4150058	ARMCUT BLACK 14 2 ply Kevlar® knitted sleeve. Thumbhole. Black color. Length : 36 cm. (Unique size)
	4150057	ARMCUT 14 BT 2 ply Kevlar® knitted sleeve. Thumbhole + mitten. Length : 36 cm. (Unique size)
	4402835	ARACUT® SLEEVES 2 ply Kevlar® knitted sleeve. Thumbhole. Length : 45 cm. (Unique size)

Additional Information

For minimum order quantities, please contact our local office. To access the test data of each reference, please refer to the technical specification documents located in each SKU.

Overview

Key Features

The Aracut® sleeves line features mediumweight sleeves made of Kevlar®.

COMFORT

The knitting technique gives the sleeves perfect support, limits the penetration of dirt and offers a good touch. The thumbhole brings a better support to the sleeves.

RESISTANCE

The Kevlar® fibre offers good cutting resistance and outstanding protection against thermal hazards in a dry environment. The dual thickness improves the cuff's mechanical and thermal performance.

Recommended Industries/Use

- Construction
- Manufacturing
- Steel and Metals

Hazards

- Abrasion
- Cut / Puncture
- Extreme Environment
- Splash

Regulations

- EN 420-2010 - General requirements
- EN 388-2003 - Mechanical risks
- EN 407-2004 - Thermal risks

Historical Brand

Perfect Fit

Warranty Information

Honeywell Safety Products warrants that its Protective Gloves are free from defects in material and workmanship. This limited warranty does not cover any product or component found to have been altered, misused, abused, tampered with or improperly maintained or to have deteriorated due to aging of any component made of rubber or any other elastomer. The limited warranty does not cover any damage, loss or expense due to damage caused by accident, abuse, improper maintenance, use or misuse of the product.

Specifications

Materials

- Kevlar®

Gauge

- Medium (10)

Resistance to heat contact

- 100°C

Maintenance / cleaning

- This article can be cleaned. For cleaning instructions, please contact Honeywell Safety Products

Storage information

- Keep gloves in their original packaging in a cool, dry, dust-free, away from sources of heat and direct light.

Training & Proper Use

Do not use these products against chemical risks or high thermal risks (more than 100°C).

Additional Information

User instructions n° 106.

Technical Support

UK: uksales@honeywell.com

Export: info-export.hsp@honeywell.com

ARACUT® SLEEVES

France: info-france.hsp@honeywell.com

Germany: info-germany.hsp@honeywell.com

Italy: info-italia.hsp@honeywell.com

Spain: info-spain.hsp@honeywell.com

Nordics: info-nordic.hsp@honeywell.com

Benelux: info-benelux.hsp@honeywell.com

Poland: info-poland.hsp@honeywell.com

Hungary: info-hungary.hsp@honeywell.com

Russia: info-russia.hsp@honeywell.com

© Honeywell International Inc.