



PRODUCT NUMBER: 2332903  
**Rig Dog™ Cold Protect**

Winter version with hook-and-loop closure. Protection of Xtreme, plus EN511 rated winter lining for cold environments.

Honeywell

Overview

Reference Number

2332903

Product Type

Gloves

Range

Cut & Sewn

Brand

Honeywell

Industry

- Building and Construction
- Mining and Quarrying
- Offshore
- Petro-chemical
- Utilities

Product Use

Back of hand impact protection and ISO level F cut protection

Features & Benefits

Feature

CoreNest™ technology

Benefit

Reinforced TPR (thermoplastic rubber) composite material with honeycomb structure to enhance the energy absorption feature on back of hand for providing improved impact protection on knuckles

Feature

Elevated finger-tip protection

Benefit

For providing enhanced impact and pinch-point protection on finger tips

Feature

Dexterity

Benefit

Impact protection is notched to allow for great flexibility and dexterity

Feature

Minimum stitching on palm

**Benefit**

Minimum stitching on palm to provide low oil permeability through palm for comfort and long lasting experience

**Feature**

Cut and sewn construction

**Benefit**

Cut and sewn construction with multilayer fabrics to provide (ISO level F) cut resistance, enhanced oil grip, dry/wet grip, and level 4 abrasion resistance

**Feature**

Quick dry, moisture wicking fabric

**Benefit**

Quick dry, moisture wicking fabric to provide sweat management for all day comfort

**Feature**

Reinforced thumb-crotch

**Benefit**

Reinforced thumb-crotch protection and durability

**Feature**

Hook-and-loop closure

**Benefit**

to customize fit, comfort and security, as well as ease in donning and doffing.

**Feature**

Available with winter lining

**Benefit**

Available with winter lining for cold environments (EN511 standard compliance)

## Technical Description

**Description**

Impact glove with cut resistant palm, hook & loop closure cuff

**Product Technology**

Honeywell CoreNest™ TPR impact pads

**Length**

25.4 cm

**Sizes**

6XS - 11XXL

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	X
Tear resistance	3
Puncture resistance	3
Cutting resistance (TDM test)	F
Impact protection	P

### EN 511- Protection in cold temperatures:

Resistance to conductive cold	1
Resistance to contact cold	2
Water permeability	X

### Packaging Label

**UOM**  
Pair

## Certifications

**EU Category PPE**  
2

**EU Certification**  
0075/797/162/02/19/0579

### REACH

#### EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

## Literature & Documents

**DATA SHEET \_Rig Dog\_Xtreme\_EMEA\_EN\_April 19**  
[http://www.honeywellsafety.com/supplementary/documents\\_and\\_downloads/gloves/4295003213/1033.aspx](http://www.honeywellsafety.com/supplementary/documents_and_downloads/gloves/4295003213/1033.aspx)

**RID DOG XTREME and COLD PROTECT Data sheet ANZ**  
[http://www.honeywellsafety.com/supplementary/documents\\_and\\_downloads/gloves/4295004612/1033.aspx](http://www.honeywellsafety.com/supplementary/documents_and_downloads/gloves/4295004612/1033.aspx)

## Maintenance

### Storage Information

Recommend product to be stored in original packaging in a cool and dry place, away from direct sunlight or other strong light. Store away from chemicals. Recommended storage temperature 10°C to 30°C.

### Care Instructions

30°C MACHINE WASH COOL. A mild commercial laundry detergent should be used. Tumble drying possible, Low temperature, and exhaust temperature max: 60°C. Do not iron. Do not bleach.

Packaging

Unit of Measure  
Pair

Quantity per Box/Pack/Case  
6

Quantity per Carton  
72

Quantity for Minimum Order  
12

Country of Origin  
China