

# HONEYWELL COCOON EVO SHELL MID

## I Extended Lifespan. Quick Wear off Notice.

The most important thing about safety shoes is the woman who wears them. Starting from this thought, Honeywell has designed Cocoon Evo, a line of women's work footwear that respects ladies' needs. Take your walking experience further and benefit from an extended lifespan. Be fully aware of how long Cocoon Evo shoes offer you the safety you deserve with their wear off indicators, a unique feature in their class. Providing improved comfort, strong safety performances, electrostatic discharge (ESD) protection, lightness, breathability as well as a modern design, Cocoon Evo safety shoes totally adapt to a lady's requirements. There are many pairs of safety shoes in the market. Meet the right one. Honeywell has put safety and convenience at ladies' feet.



### SHELL MID S3 HI CI SRC ESD

- 100% non-metallic toecap
- Mid-cut style
- Nubuck leather upper
- 3D mesh with foam lining
- Textile anti-perforation interlayer
- EVA/TPU sole
- HI and CI markings: resistance to inimical environments – heat insulation and cold insulation of the sole complex
- ESD marking: electrical resistance
- ESD (EN 61340:5-1:2016) S3 HI CI SRC ESD

## BEYOND COMPLIANCE, ABOVE YOUR EXPECTATIONS

Tests have shown that Shell Mid performs beyond certification levels, providing ladies with safety and comfort that exceed their requirements\*:

### MORE PROTECTION

- **34%** more impact resistance than the standard requirements. Shell Mid has an impact resistance amounting to 18.75, compared to the required level of  $\geq 14$  mm.
- **31%** more slip resistance (flat position) than SRA\*\* requirements. Shell Mid recorded a value of 0.42, up against the required level of  $\geq 0.32$ .
- **68%** more slip resistance (heel area) than SRA requirements. Shell Mid provides a figure amounting to 0.47, up against the required level of  $\geq 0.28$ .

### MORE DURABLE LINING

- **467%** more tear strength against standard requirements. Shell Mid recorded a value of 87 N, exceeding the standard requirement of  $\geq 15$  N.
- **1,880%** more water permeability than standard requirements. Shell Mid provides a water permeability index of 39.6 mg/ (cm<sup>2</sup>.h), exceeding the required level of  $\geq 2$  mg/ (cm<sup>2</sup>.h).

### MORE BREATHABLE UPPER

- **663%** more water permeability than the standard requirements. Shell Mid has an average value of 6.1 mg/(cm<sup>2</sup>.h), up against the level of  $\geq 0.8$  mg/cm<sup>2</sup>.h), required by the standard.
- **296%** more water vapor permeability and absorption. Shell Mid recorded a water coefficient of 59.35 mg/cm<sup>2</sup>, up against the standard requirement of  $\geq 15$  mg/cm<sup>2</sup>.

\*) The values reflect the ESD (EN 61340:5-1:2016) standard test results for the Honeywell Cocoon Evo range performed on EU size 42 samples.  
\*\*) Slip resistance on floors with ceramic tiles wetted with sodium lauryl ether sulfate (SLS) solution.

# THE FEATURES THAT MAKE THE DIFFERENCE

## TOECAP

- Non-metallic material

## SOLE - TECHNICAL DATA

- Textile anti-perforation interlayer
- 3 wear-off indicators on the outer layer
- Heel shock absorption system
- EVA midsole, comfort layer
- **TPU outsole skin**
- **TPU wear-off indicator inserts**
- **Wide, deep and self-cleaning relief providing anti-slip resistance**
- Adhesion coefficient compliant with ESD (EN 61340:5-1:2016)
- On steel floor:
  - Heel: 0.24 (minimum standard 0.13)
  - Flat: 0.18 (minimum standard 0.18)
- On ceramic floor:
  - Heel: 0.47 (minimum standard 0.28)
  - Flat: 0.42 (minimum standard 0.32)
- Energy absorption capacity: >20 J
- Abrasion resistance: loss in volume <150 mm<sup>3</sup> (under a 10 Newtons (1 kg) load)
  - Elongation at break: 650%
  - Resistance to repeated flexion optimized: >30,000
- Flexometer tested-standard: >30,000
- Enhanced hydrocarbon resistance
- Resistance to acids and bases: limited to low concentration

## TECHNICAL SPECIFICATIONS AND STANDARDS:

- European Regulation: (EU) 2016/425\*
- Standard: ESD (EN 61340:5-1:2016)\*\*
- Quality assurance: ISO 9001 Version 2015\*\*\*
- Marking: S3 HI CI SRC ESD
- Average weight for 1 shoe 42 size: 596 g

\*) <https://osha.europa.eu/en/safety-and-health-legislation>

\*\*) <https://www.iso.org/home.html>

\*\*\*) <https://group.bureauveritas.com/>

## OUTSOLE SLIP RESISTANCE PERFORMANCE

MARKING	SURFACE	LUBRICANT	FRICTION FACTOR: FLAT
SRA	Ceramic plates	Sodium lauryl sulfate	0.42 (minimum requirement 0.32)
SRB	Steel	Glycerol	0.18 (mimimum standard 0.18)
SRC	Meets requirements of the above 2 tests (SRA plus SRB)		

## ORDERING INFORMATION

DESCRIPTION	REF.	SIZE
Shell Mid S3 HI CI SRC ESD	65 516 15	35-42

### For More Information

[www.honeywellsafety.com](http://www.honeywellsafety.com)

#### HONEYWELL SAFETY PRODUCTS UNITED KINGDOM

Honeywell Safety Products UK LTD  
Edison Road  
Basingstoke RG21 6QD  
Phone: +44 (0) 1256 693 200  
Fax: +44 (0) 1256 693 300  
Email: [info-uk.hsp@honeywell.com](mailto:info-uk.hsp@honeywell.com)

#### HONEYWELL SAFETY PRODUCTS NORDICS

Honeywell Safety Products Nordic AB  
Strandbadsvägen 15  
SE-252 29 Helsingborg – Sverige  
Phone: +46 (0) 424480433  
Email: [info-nordic.hsp@honeywell.com](mailto:info-nordic.hsp@honeywell.com)

#### HONEYWELL SAFETY PRODUCTS BENELUX

Honeywell Safety Products Benelux BV  
Hermeslaan 1H – 1831 Diegem  
Phone: +32 (0) 2 728 2117  
Fax: +32 (0) 2 728 2396  
Email: [info-benelux.hsp@honeywell.com](mailto:info-benelux.hsp@honeywell.com)