

5000 SERIES COMFORT

THE BEST COMBINATION IN TERMS OF PERFORMANCE FOR STANDARD WORKING CONDITIONS

- Nose-bridge: improved individual fit.
- High performance exhalation valve: easier breathing during periods of prolonged use.
- Double stapled elastic strap: strong in case of repeated removals, without touching the filtering section.
- Exclusively designed seal adapted to the nose: good fit and comfort throughout the day.
- Hypoallergenic: minimal risk of irritation.



INDUSTRY & APPLICATIONS

- Automotive and Part Manufacturer
- Building and construction
- Food Industries
- Foundry
- Iron and steel industry
- Medical and Pharmaceutical
- Mining and Quarrying
- Textile industry
- Sanding or Cutting wood



DESCRIPTION		CERTIFICATIONS		MAINTENANCE	
Product Type	Respiratory Protection	EC Category PPE:	3	Life Cycle:	3 years
Line	Molded masks	Quality Assurance:	ISO 9001 / 2000	Storage Information:	Temperature range of storage conditions: -20°C/+40°C
Range	Disposable	Certifications:	EN 149:2001+A1:2009	Maximum relative humidity of storage conditions:	Less than 80-95%

- ✓ Latex free
- ✓ PVC Free
- ✓ Silicone Free

MAXIMUM USAGE LEVEL

Can be used in atmospheres containing solid and/or liquid aerosols in concentrations corresponding to the average toxicity. "NR" (Non Reusable) marked, it can be used one single shift (according to EN 149:2001+A1:2009). Certain restrictions or limitations may apply in the case of specific contaminants. "D" marked: Dolomite tested, designed to resist clogging.

LIMITATIONS TO USE

This single-use filtering half-mask should NOT be used in the following situations:

- Oxygen concentration is less than 17% (oxygen-deficient atmospheres)
- Contaminants or their concentrations are unknown or are immediately dangerous to life or health
- Contaminants concentrations exceed levels fixed by applicable health and safety standards
- In the presence of toxic or radio-active contaminants
- In the presence of gases or vapors
- In the explosive atmospheres
- Fire fighting

REFERENCE	NAME	SIZE	CLASSIFICATION	EXHALATION VALVE	SEAL	FASTENERS	PACKAGING BOX/CASE/PALLET	MOQ
1007221	Honeywell 5185	M/L	FFP1 NR D	No	Nasal	Elastic	20/200/5400	200
1007222	Honeywell 5186	M/L	FFP1 NR D	Yes	Nasal	Elastic	20/200/5400	200
1007223-V2	Honeywell 5208	M/L	FFP2 NR D	No	Nasal	Elastic	20/200/5400	200
1007224-V2	Honeywell 5209	M/L	FFP2 NR D	Yes	Nasal	Elastic	20/200/5400	200
1007225-V2	Honeywell 5311	M/L	FFP3 NR D	Yes	Nasal	Elastic	20/200/5400	200

For more information

sps.honeywell.com

UNITED KINGDOM

Honeywell Respiratory Safety Products
C.S. 55288 - 95958 ROISSY CDG Cedex
ZI PARIS NORD II
33, Rue des Vanesses – VILLEPINTE France
Phone: +33 (0)1 49 90 79 79
Email: info-uk.hsp@honeywell.com

www.honeywell.com

HPPE Respiratory EU 5000 Series Comfort Datasheet | 08/22
© 2022 Honeywell International Inc.

