

TECHNICAL DATA

40 cal/cm² Lift Front Hood with PrismShield

Technical Information Sheet

Honeywell Salisbury's Lift Front Hood is intended to provide protection against the heat and blast release in an arc flash event rated 40 cal/cm² or lower. The face shield and shroud parts are considered pieces of the full unit and both must be worn in order to provide full protection

PART NUMBERS

- LFH40-SPL: Lift Front Hood with PrismShield, regular shroud
- LFH40PLT-SPL: Lift Front Hood with PrismShield, premium light weight shroud



LFH40-SPL

STANDARDS INFORMATION

AGENCY SPECIFICATION

ASTM F2178

STANDARD TEST METHOD FOR DETERMINING THE ARC RATING AND STANDARD SPECIFICATION FOR EYE OR FACE PROTECTIVE PRODUCTS

ANSI Z87.1

OCCUPATIONAL AND EDUCATIONAL PERSONAL EYE AND FACE PROTECTION DEVICES

NFPA 70E

STANDARD FOR ELECTRICAL SAFETY IN THE WORKPLACE®

TECHNICAL DATA

MATERIALS INFORMATION

PHYSICAL SPECIFICATIONS	
VIEWING AREA	7.5" x 20"
TOTAL WEIGHT (REGULAR)	2.80 LBS (1.27 KG)
TOTAL WEIGHT (PLT)	2.65 LBS (1.20 KG)
DIMENSIONS	20"H X 10.5"W X 11"D
FLASH LIGHT ATTACHEMENT SLOTS	2
LENS TECHNOLOGY	PRISMSHIELD
LENS COLOR	BRONZE
LENS MATERIAL	POLYCARBONATE
LENS SPECIALITY COATING	ANTI-FOG, ANTI-SCRATCH
SHROUD MATERIAL (REGULAR)	COTTON/NYLON BLEND
SHROUD MATERIAL (PLT)	ARAMID BLEND
SHROUD WEIGHT (REGULAR)	9 OZ/YD ² OVER 9 OZ/YD ²
SHROUD WEIGHT (PLT)	5 OZ/YD ² OVER 6 OZ/YD ²
ATPV	40 CAL/CM ²

ACCESSORIES & SPARE PARTS

ACCESSORY & SPARE PART ORDERING INFORMATION	
PART NUMBER	ITEM DESCRIPTION
LFH40LENS-SPL	Replacement lens
LFH40CP	Replacement chin guard
LFH40UF	Upper frame replacement
SHRD-40A	Replacement shroud, regular
SHRD-40PLT	Replacement shroud, PLT
SN10R03	Replacement N10 hard hat
FLKIT	Attachable task light kit
AS BAG	Face Shield storage bag (21" L, 19" W, 14" H)
SK BAG	Large Storage Bag (24" L, 20" W, 15" H)
SKBACKPACK	Reinforced specialty backpack (14" L, 8" W, 18" H)

For more information
www.salisburybyhoneywell.com

**Honeywell Salisbury
USA**
101 E Crossroads Pkwy Ste A
Bolingbrook, IL 60440
Phone: 877.406.4501
Fax: 866.824.4922
www.honeywell.com