

C-Clamp with RocketLock Technology

Technical Information Sheet



The Honeywell Salisbury™ C-Clamp with RocketLock™ technology features hyper-fast installation that is unmatched within the industry. Designed with a spring-loaded jaw that snaps closed instantly, the clamp requires only one-half turn to lock securely in place to the proper torque specification.

STANDARDS INFORMATION

ASTM F855-09	
ASTM TYPE	I
ASTM CLASS	A
ASTM GRADE	5H

For more information
www.salisburybyhoneywell.com

**Honeywell Salisbury
USA**
101 E Crossroads Pkwy Ste A
Bolingbrook, IL 60440
Phone: 877.406.4501
Fax: 866.824.4922
www.honeywell.com

MECHANICAL RATINGS

MECHANICAL SPECIFICATIONS

Clamp Body	Aluminum
Jaw Type	.75 inch smooth
Ferrule Connection	Tapped for 5/8-11 UNC threaded ferrules

ELECTRICAL RATING

ELECTRICAL RATING SPECIFICATIONS

Continuous Current	400 RMS AMPS, 60 Hz
Fault Current 15 Cycles	43,000 AMPS
Fault Current 30 Cycles	30,000 AMPS

MAIN LINE RANGE

MAIN LINE SPECIFICATIONS

Min Size	.19 inch (4.8 mm)
Max Size	.75 inch (19 mm)

ORDERING INFORMATION

PRODUCT ORDERING INFORMATION

PART NUMBER	DESCRIPTION	ASTM GRADE	WEIGHT
22945	SMALL C-CLAMP WITH ROCKETLOCK	5H / A	1.7 lbs. (.78 kgs)

For more information
www.salisburybyhoneywell.com

**Honeywell Salisbury
USA**
101 E Crossroads Pkwy Ste A
Bolingbrook, IL 60440
Phone: 877.406.4501
Fax: 866.824.4922
www.honeywell.com