



HONEYWELL SALISBURY MODEL 24650-ES FLAT FACE CLAMP WITH EYESCREW

TECHNICAL DATA SHEET

Honeywell Salisbury™ high rated ground clamps which offer lineman exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

CERTIFICATION AND TESTING

ASTM Standard	ASTM Type	ASTM Class	ASTM Grade
ASTM F855	I	B	5 / 5H

MECHANICAL DESCRIPTION

Clamp Material	Eyescrew Material	Thread Type	Jaw Type	Ferrule Connection
Aluminum	Bronze	V Thread	1.54" Serrated Jaw	Tapped for 5/8" - 11 UNC Threaded Ferrules

ELECTRICAL RATING

Continuous Current Rating, A RMS, 60 Hz	Fault Current, 15 Cycles (AMPS)	Fault Current, 30 Cycles (AMPS)
400	47,000 High X/R (Grade 5H) 43,000 (Grade 5)	30,000 (Grade 5)

MAIN LINE RANGE

Minimum Size	Maximum Size
#8 (.125 inch / 3.1 mm Diameter) (.06 inch / 1.5 mm) Flat, Square, Round	1431 MCM ACSR (1.54 inch / 39.1 mm Diameter) (1.26 inch / 32 mm) Flat, Square, Round

ORDERING INFORMATION

Part Number	Description	Weight
24650-ES	1.5" Serrated Flat Face Clamp with Eyescrew and Strain Relief Sleeve	2.28 lbs. / 1.03 kgs

Recommend copper shrouded ferrule model 24714-ES be used for 5H applications.