



# HONEYWELL SALISBURY MODEL 24650-ES FLAT FACE CLAMP WITH EYESCREW

## TECHNICAL DATA SHEET

Honeywell Salisbury™ high rated ground clamps which offer linemen exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

### CERTIFICATION AND TESTING

| ASTM Standard | ASTM Type | ASTM Class | ASTM Grade |
|---------------|-----------|------------|------------|
| ASTM F855     | I         | B          | 5 / 5H     |

### MECHANICAL DESCRIPTION

| Clamp Material | Eyescrew Material | Thread Type | Jaw Type           | Ferrule Connection                         |
|----------------|-------------------|-------------|--------------------|--|
| Aluminum       | Bronze            | V Thread    | 1.50" Serrated Jaw | Tapped for 5/8" - 11 UNC Threaded Ferrules |

### ELECTRICAL RATING

| Continuous Current Rating, A RMS, 60 Hz | Fault Current, 15 Cycles (AMPS)                | Fault Current, 30 Cycles (AMPS) |
|---|--|---------------------------------|
| 400                                     | 47,000 High X/R (Grade 5H)<br>43,000 (Grade 5) | 30,000 (Grade 5)                |

## MAIN LINE RANGE

| Minimum Size  | Maximum Size  |
|---|---|
| #8 (.125 inch / 3.1 mm Diameter)<br>(.06 inch / 1.5 mm) Flat, Square, Round | 1431 MCM ACSR (1.50 inch / 39.1 mm Diameter)<br>(1.26 inch / 32 mm) Flat, Square, Round |

## ORDERING INFORMATION

| Part Number | Description  | Weight               |
|-------------|--|----------------------|
| 24650-ES    | 1.5" Serrated Flat Face Clamp with Eyescrew and Strain Relief Sleeve | 2.28 lbs. / 1.03 kgs |

Recommend copper shrouded ferrule model 24714-ES be used for 5H applications.