



# **HONEYWELL SALISBURY**

## **MODEL 24714-ES**

### **4/0 COPPER SHROUDED**

### **THREADED FERRULE**

#### **TECHNICAL DATA SHEET**

Honeywell Salisbury™ high rated ground components which offer lineman exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

#### **CERTIFICATION AND TESTING**

ASTM Standard	ASTM Grade
ASTM F855	5 / 5H

#### **MECHANICAL DESCRIPTION**

Material	Size	Thread
Tin-Plated Copper	4/0	5/8" - 11 UNC 2A

## DIMENSIONS

OAL	Thread	Body	Shroud
4.93" (125.2 mm)	2.07" (52.58 mm)	2.82" (71.6 mm)	1.3" (33 mm)

## ELECTRICAL RATING

Continuous Current Rating, A RMS, 60 Hz	Fault Current, 15 Cycles (AMPS)	Fault Current, 30 Cycles (AMPS)
400	47,000 High X/R (Grade 5H) 43,000 (Grade 5)	30,000 (Grade 5)

## ORDERING INFORMATION

Part Number	Description	Weight
24714-ES	4/0 Shrouded Ferrule	.06 lbs. / .027 kgs

Recommended for use with Model 24649-ES and 24650-ES Flat Face Clamps for 5H applications.