HONEYWELL SALISBURY
MODEL 24668-ES
350 KCMIL COPPER THREADED FERRULE

TECHNICAL DATA SHEET

Honeywell Salisbury™ high rated ground components which offer lineman exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

CERTIFICATION AND TESTING

ASTM Standard	ASTM Grade
ASTM F855	7/ 7H

MECHANICAL DESCRIPTION

Material	Size	Thread
Tin-Plated Copper	350 KCMIL	3/4” – 10 UNC 2A

DIMENSIONS

OAL	Thread	Body
6.75” (171.4 mm)	1.75” (44.5 mm)	4.75” (120.6 mm)

ELECTRICAL RATING

Continuous Current Rating, A RMS, 60 Hz	Fault Current, 15 Cycles (AMPS)		Fault Current, 30 Cycles (AMPS)
550	68,000 High X/R (Grade 7H) (Grade 7)	74,000	54,000 (Grade 7)

ORDERING INFORMATION

Part Number	Description	Weight
24668-ES	350 KCMIL Copper Ferrule	1.18 lbs. / .53 kgs

For More Information Visit:
https://sps.honeywell.com/us/en/products/safety/electrical-safety
Honeywell Salisbury USA
2520 South Walnut Road
Freeport, IL 61032

Phone within US: 877-406-4501
Phone outside US: 630-343-3800
Product inquiries (US/CAN): cssd@honeywell.com
Product inquiries (INTL): customerservicesalisburyintl@honeywell.com
Orders: salisburyorders@honeywell.com