



HONEYWELL SALISBURY

MODEL 24610-ES

MODEL 24710-ES

DUCKBILL CLAMPS

TECHNICAL DATA SHEET

Honeywell Salisbury™ high rated ground clamps which offer linemen exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

CERTIFICATION AND TESTING

ASTM Standard	ASTM Type	ASTM Class	ASTM Grade
ASTM F855	1	B	5 / 5H

MECHANICAL DESCRIPTION

Clamp Material	Eyescrew Material	Thread Type	Jaw Type	Ferrule Connection
Aluminum	Bronze	V Thread	1.66" Serrated Jaw	Tapped for 5/8" - 11 UNC Threaded Ferrules

ELECTRICAL RATING

Continuous Current Rating, A RMS, 60 Hz	Fault Current, 15 Cycles (AMPS)	Fault Current, 30 Cycles (AMPS)
400	47,000 High X/R (Grade 5H) 43,000 (Grade 5)	30,000 (Grade 5)

MAIN LINE RANGE

Minimum Size	Maximum Size
#6 (.19 inch / 4.8 mm Diameter)	1590 MCM ACSR (1.54 inch / 39 mm Diameter)

ORDERING INFORMATION

Part Number	Description	Weight
24610-ES	1.66" Serrated Duckbill Clamp with Strain Relief Sleeve	1.7 lbs. / .81 kgs
24710-ES	1.66" Serrated Duckbill Clamp with no Strain Relief Sleeve	1.6 lbs. / .72 kgs

For More Information Visit:
<https://sps.honeywell.com/us/en/products/safety/electrical-safety>
Honeywell Salisbury USA
2520 South Walnut Road
Freeport, IL 61032

Phone within US: 877-406-4501
Phone outside US: 630-343-3800
Product inquiries (US/CAN): cssd@honeywell.com
Product inquiries (INTL): customerservicesalisburyintl@honeywell.com
Orders: salisburyorders@honeywell.com