



HONEYWELL SALISBURY

MODEL 24640-ES

MODEL 24711-ES

DUCKBILL CLAMPS

TECHNICAL DATA SHEET

Honeywell Salisbury™ high rated ground clamps which offer linemen exceptional reliability and ease-of-use along with the confidence of proven protective compliance.

CERTIFICATION AND TESTING

ASTM Standard	ASTM Type	ASTM Class	ASTM Grade
ASTM F855	1	A	5 / 5H

MECHANICAL DESCRIPTION

Clamp Material	Eyescrew Material	Thread Type	Jaw Type	Ferrule Connection
Aluminum	Bronze	V Thread	1.1" Smooth Jaw	Tapped for 5/8" - 11 UNC Threaded Ferrules

ELECTRICAL RATING

Continuous Current Rating, A RMS, 60 Hz	Fault Current, 15 Cycles (AMPS)	Fault Current, 30 Cycles (AMPS)
400	47,000 High X/R (Grade 5H) 43,000 (Grade 5)	30,000 (Grade 5)

MAIN LINE RANGE

Minimum Size	Maximum Size
#6 (.16 inch / 4 mm Diameter)	900 MCM ACSR (1.162 inch / 29.5 mm Diameter)

ORDERING INFORMATION

Part Number	Description	Weight
24640-ES	1.1" Smooth Duckbill Clamp with Strain Relief Sleeve	1.5 lbs. / .7 kgs
24711-ES	1.1" Smooth Duckbill Clamp with no Strain Relief Sleeve	1.4 lbs. / .64 kgs