

## Aluminum Duck Bill Grounding Clamp – Model 22998

Technical Information Sheet



Rugged smooth-action clamp. Snaps on to connector for ease in tightening.

### STANDARDS INFORMATION

ASTM F855-09

ASTM TYPE 1

ASTM CLASS B

ASTM GRADE 5

#### For more information

[www.salisburybyhoneywell.com](http://www.salisburybyhoneywell.com)

#### Honeywell USA

101 E Crossroads Pkwy Ste A

Bolingbrook, IL 60440

Phone: 877.406.4501

Fax: 866.824.4922

[www.honeywell.com](http://www.honeywell.com)

**MECHANICAL RATINGS**

MECHANICAL SPECIFICATIONS

Clamp Body	Aluminum
Eyescrew	Bronze Alloy
Thread Type	V thread
Jaw Type	1.66 inch serrated jaw
Ferrule Connection	Tapped for 5/8-11 UNC Threaded Ferrules
Recommended Torque	250 in. - lb

**ELECTRICAL RATING**

ELECTRICAL RATING SPECIFICATIONS

Continuous Current	400 RMS AMPS, 60 Hz
Fault Current 15 Cycles	43,000 AMPS
Fault Current 30 Cycles	30,000 AMPS

**MAIN LINE RANGE**

MAIN LINE SPECIFICATIONS

Min Size	#6 (.16 inch / 4 mm Diameter)
Max Size	1590 MCM ACSR (1.66 inch / 42 mm Diameter)

**ORDERING INFORMATION**

PRODUCT ORDERING INFORMATION

PART NUMBER	DESCRIPTION	ASTM GRADE	WEIGHT
22998	1.66" Serrated Jaw Aluminum Duck Bill	5 / B	1.5 lbs. (.7 kgs)

**For more information**  
[www.salisburybyhoneywell.com](http://www.salisburybyhoneywell.com)

**Honeywell  
USA**  
101 E Crossroads Pkwy Ste A  
Bolingbrook, IL 60440  
Phone: 877.406.4501  
Fax: 866.824.4922  
[www.honeywell.com](http://www.honeywell.com)