

HONEYWELL SALISBURY DUCKBILL CLAMPS

.96" DUCKBILL CLAMPS

Part Number	1793-ES	21080-ES	1797-ES
Size	0.96"	0.96"	0.96"
Description	Bronze clamp w/strain relief sleeve, Smooth Jaw	Bronze clamp w/o strain relief sleeve, Smooth Jaw	Bronze clamp w/strain relief sleeve, Smooth Jaw, Mounted on 6' Fiberglass Stick
Duckbill Style	Gravity Actuated	Gravity Actuated	Gravity Actuated
Clamp Material	Bronze	Bronze	Bronze
Eyscrew Material	Bronze	Bronze	Bronze
Screw Style	V Thread	V Thread	V Thread
Screw Grip	Eye	Eye	Stick Mounted
Jaw Style	Smooth	Smooth	Smooth
Ferrule Type	Threaded	Threaded	Threaded
Parking Stand	Model 2093-ES	Model 2093-ES	Model 2093-ES
Main Line Range	556 MCM ACSR to #6 .96" - .16" (24 mm - 4 mm)	556 MCM ACSR to #6 .96" - .16" (24 mm - 4 mm)	556 MCM ACSR to #6 .96" - .16" (24 mm - 4 mm)
Strain Relief	Yes	Yes	Yes
Strain Relief Sleeve	Yes	No	Yes
Weight	1.3 lbs. / .6 kgs	1.1 lbs. / .5 kgs	4.3 lbs. / 2 kgs
Grade	4	4	4
Class	A	A	A
Continuous Current (RMS), 60 Hz	350	350	350
Fault Current - 15 Cycles (AMPS)	34,000 (Grade 4)	34,000 (Grade 4)	34,000 (Grade 4)
Fault Current - 30 Cycles (AMPS)	25,000 (Grade 4)	25,000 (Grade 4)	25,000 (Grade 4)

HONEYWELL SALISBURY DUCKBILL CLAMPS

1.1" DUCKBILL CLAMPS (THREADED FERRULE)

	☆ NEW ☆			
Part Number	21030-ES	21059-ES	21081-ES	24640-ES
Size	1.1"	1.1"	1.1"	1.1"
Description	Aluminum clamp w/strain relief sleeve, Smooth Jaw	Aluminum clamp w/o strain relief sleeve, Smooth Jaw	Aluminum clamp w/strain relief sleeve, Smooth Jaw, Mounted on 6' Fiberglass Stick	Aluminum Clamp w/strain relief sleeve, Smooth Jaw
Duckbill Style	Spring Loaded	Spring Loaded	Spring Loaded	Spring Loaded
Clamp Material	Aluminum	Aluminum	Aluminum	Aluminum
Eyescrew Material	Bronze	Bronze	Bronze	Bronze
Screw Style	V Thread	V Thread	V Thread	V Thread
Screw Grip	Eye	Eye	Stick Mounted	Eye
Jaw Style	Smooth	Smooth	Smooth	Smooth
Ferrule Type	Threaded	Threaded	Threaded	Threaded
Parking Stand	Model 21754-ES	Model 21754-ES	Model 21754-ES	Model 21754-ES
Main Line Range	795 MCM ACSR to #6 1.1" - .16" (28 mm - 4 mm)	795 MCM ACSR to #6 1.1" - .16" (28 mm - 4 mm)	795 MCM ACSR to #6 1.1" - .16" (28 mm - 4 mm)	900 MCM ACSR to #6 1.162" - .16" (29.5 mm - 4 mm)
Strain Relief	Yes	Yes	Yes	Yes
Strain Relief Sleeve	Yes	No	Yes	Yes
Weight	1.1 lbs. / .5 kgs	1.0 lbs. / .5 kgs	4.3 lbs. / 2 kgs	1.5 lbs. / .7 kgs
Grade	5	5	5	5
Class	A	A	A	5 / 5H
Continuous Current (RMS), 60 Hz	400	400	400	400
Fault Current - 15 Cycles (AMPS)	43,000 (Grade 5)	43,000 (Grade 5)	43,000 (Grade 5)	47,000 High X/R (Grade 5H) 43,000 (Grade 5)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)

HONEYWELL SALISBURY DUCKBILL CLAMPS

1.1" DUCKBILL CLAMPS (PIN STYLE FERRULE)

Part Number	24404-ES	24407-ES	761E-ES
Size	1.1"	1.1"	1.13"
Description	Aluminum clamp w/o strain relief sleeve, Smooth Jaw	Aluminum clamp w/o strain relief sleeve, Smooth Jaw, Mounted on 6' Fiberglass Stick	Aluminum clamp w/o strain relief, Smooth Jaw
Duckbill Style	Spring Loaded	Spring Loaded	Spring Loaded
Clamp Material	Aluminum	Aluminum	Aluminum
Eyscrew Material	Bronze	Bronze	Stainless Steel
Screw Style	V Thread	V Thread	V Thread
Screw Grip	Eye	Stick Mounted	Eye
Jaw Style	Smooth	Smooth	Smooth
Ferrule Type	Pin Style	Pin Style	Pin
Parking Stand	Model 21754-ES	Model 21754-ES	No
Main Line Range	795 MCM ACSR to #6 1.1" - .16" (28 mm - 4 mm)	795 MCM ACSR to #6 1.1" - .16" (28 mm - 4 mm)	795 MCM ACSR to #6 1.13" - .19" (28.7 mm - 4 mm)
Strain Relief	Yes	Yes	No
Strain Relief Sleeve	No	No	No
Weight	1.5 lbs. / .68 kgs	4.5 lbs. / 2.05 kgs	1.3 lbs. / 0.59 kgs
Grade	5	5	3
Class	A	A	A
Continuous Current (RMS), 60 Hz	400	400	300
Fault Current - 15 Cycles (AMPS)	43,000 (Grade 5)	43,000 (Grade 5)	27,000 (Grade 3)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)	20,000 (Grade 3)

HONEYWELL SALISBURY DUCKBILL CLAMPS

1.13" DUCKBILL CLAMPS (THREADED FERRULE)

Part Number	767E-ES	768E-ES
Size	1.13"	1.13"
Description	Aluminum clamp w/o strain relief, Smooth Jaw	Aluminum clamp w/o strain relief, Smooth Jaw, Open Jaw
Duckbill Style	Spring Loaded	Open Jaw
Clamp Material	Aluminum	Aluminum
Eyscrew Material	Stainless Steel	Stainless Steel
Screw Style	V Thread	V Thread
Screw Grip	Eye	Eye
Jaw Style	Smooth	Smooth
Ferrule Type	Threaded	Threaded
Parking Stand	No	No
Main Line Range	795 MCM ACSR to #6 1.13" - .19" (28.7 mm - 4 mm)	795 MCM ACSR to #6 1.13" - .19" (28.7 mm - 4 mm)
Strain Relief	No	No
Strain Relief Sleeve	No	No
Weight	1.4 lbs. / .63 kgs	1.4 lbs. / .63 kgs
Grade	3	3
Class	A	A
Continuous Current (RMS), 60 Hz	300	300
Fault Current - 15 Cycles (AMPS)	27,000 (Grade 3)	27,000 (Grade 3)
Fault Current - 30 Cycles (AMPS)	20,000 (Grade 3)	20,000 (Grade 3)

HONEYWELL SALISBURY DUCKBILL CLAMPS

1.63" DUCKBILL CLAMPS (THREADED FERRULE)

Part Number	760006E-ES	760SR6E-ES	760SR6PSE-ES	760SRS6E-ES
Size	1.63"	1.63"	1.63"	1.63"
Description	Aluminum clamp w/o strain relief, Smooth Jaw	Aluminum clamp w/strain relief, Smooth Jaw	Aluminum clamp w/strain relief, Smooth Jaw, Aluminum Parking Stand	Aluminum clamp w/strain relief, Serrated Jaw
Duckbill Style	Spring Loaded	Spring Loaded	Spring Loaded	Spring Loaded
Clamp Material	Aluminum	Aluminum	Aluminum	Aluminum
Eyescrew Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Screw Style	V Thread	V Thread	V Thread	V Thread
Screw Grip	Eye	Eye	Eye	Eye
Jaw Style	Smooth	Smooth	Smooth	Serrated
Ferrule Type	Threaded	Threaded	Threaded	Threaded
Parking Stand	No	No	Yes	No
Main Line Range	954 MCM ACSR to #6 1.63" - .19" (41 mm - 4.8 mm)	954 MCM ACSR to #6 1.63" - .19" (41 mm - 4.8 mm)	954 MCM ACSR to #6 1.63" - .19" (41 mm - 4.8 mm)	954 MCM ACSR to #6 1.63" - .19" (41 mm - 4.8 mm)
Strain Relief	No	Yes	Yes	Yes
Strain Relief Sleeve	No	No	No	No
Weight	3.0 lbs. / 1.36 kgs	2.2 lbs. / 1.0 kgs	2.5 lbs. / 1.14 kgs	2.2 lbs. / 1.0 kgs
Grade	5	5	5	5
Class	A	A	A	B
Continuous Current (RMS), 60 Hz	400	400	400	400
Fault Current - 15 Cycles (AMPS)	43,000 (Grade 5)	43,000 (Grade 5)	43,000 (Grade 5)	43,000 (Grade 5)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)

HONEYWELL SALISBURY DUCKBILL CLAMPS

1.66" DUCKBILL CLAMPS (THREADED FERRULE)

	★NEW★				
Part Number	2553-ES	1853-ES	22998-ES	1855-ES	24610-ES
Size	1.66"	1.66"	1.66"	1.66"	1.66"
Description	Aluminum clamp w/o strain relief sleeve, Serrated Jaw	Aluminum clamp w/strain relief sleeve, Serrated Jaw	Aluminum clamp w/strain relief sleeve, Serrated Jaw	Aluminum clamp w/strain relief sleeve, Serrated Jaw, Mounted on 6' Fiberglass Stick	Aluminum clamp w/strain relief sleeve, Serrated Jaw
Duckbill Style	Spring Loaded	Spring Loaded	Spring Loaded	Spring Loaded	Spring Loaded
Clamp Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Eyescrew Material	Bronze	Bronze	Bronze	Bronze	Bronze
Screw Style	Acme	Acme	V Thread	Acme	V Thread
Screw Grip	Eye	Eye	Eye	Stick Mounted	Eye
Jaw Style	Serrated	Serrated	Serrated	Serrated	Serrated
Ferrule Type	Threaded	Threaded	Threaded	Threaded	Threaded
Parking Stand	Model 21754-ES	Model 21754-ES	Model 21754-ES	Model 21754-ES	Model 21754-ES
Main Line Range	1590 MCM ACSR to #6 1.66" - .16" (42 mm - 4 mm)	1590 MCM ACSR to #6 1.66" - .16" (42 mm - 4 mm)	1590 MCM ACSR to #6 1.66" - .16" (42 mm - 4 mm)	1590 MCM ACSR to #6 1.66" - .16" (42 mm - 4 mm)	1590 MCM ACSR to #6 1.54" - .19" (39 mm - 4.8 mm)
Strain Relief	Yes	Yes	Yes	Yes	Yes
Strain Relief Sleeve	No	Yes	Yes	Yes	Yes
Weight	1.4 lbs. / .6 kgs	1.5 lbs. / .5 kgs	1.5 lbs. / .5 kgs	4.7 lbs. / 2.1 kgs	1.7 lbs. / .81 kgs
Grade	5	5	5	5	5
Class	B	B	B	B	5 / 5H
Continuous Current (RMS), 60 Hz	400	400	400	400	400
Fault Current - 15 Cycles (AMPS)	43,000 (Grade 5)	43,000 (Grade 5)	43,000 (Grade 5)	43,000 (Grade 5)	47,000 High X/R (Grade 5H) 43,000 (Grade 5)
Fault Current - 30 Cycles (AMPS)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)	30,000 (Grade 5)