

Miller 650 Series

Non-Stretch Harnesses

SP104 Rev. B

Materials

| | |
|------------------------|------------------------------------------------------------------------|
| Webbing | 1-3/4" Polyester |
| Minimum Tensile | 5000 lbs. on webbing |
| Thread: | 6 cord bonded 3 strand polyester thread. Minimum tensile of 42 lbs. |
| Grommets | Brass |
| Hardware | Steel Minimum Tensile strength |
| D-Ring | 5000 lbs. (22kN) |
| Buckles | 4000 lbs. (18kN) |

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

| | |
|--------------------------|-------------------|
| Max Working Load: | 400 lbs -181.4kg |
| Label Materials | Lexan and Valeron |

Certification

Meets applicable ANSI, OSHA and CSA requirements

Harness Description Keys

Webbing

D = DuraFlex Stretchable Webbing
DP = DuraFlex Python Webbing
K = Kevlar Webbing
P = Polyester Webbing

D-Rings

B = Sliding Back D-Ring
FD = Front D-Ring
F = Front O-Ring
H = Shoulder D-Rings
S = Side Positioning D-Rings
W = Sliding Back web D-Ring
X = D-Ring Web Extension

Special Features

AB = Attached Waist Belt
AL = Adjustable Belt Loops
BL = Belt Loops
BP = Back Pad
HP = Shoulder Pads
LP = Leg Pads
LR = Lanyard Ring
RB = Removable Waist Belt
SP = Sub-Pelvic Strap
SR = Self Rescue Loops
SS = Saddle Seat
TO = Tool Belt Buckles

Shoulder/Leg Buckles

FB = Friction Buckles
MB = Mating Buckles
TB = Tongue Buckles



| Model No. | Web Type | D-Rings | Shoulder Straps | Leg Straps | Chest Strap | Special Features | Weight |
|-----------|----------|---------|-----------------|------------|-------------|------------------|-------------------|
| 650* | P | B | FB | MB | MB | BL, SP, LR | 2.90 lbs. (1.3kg) |
| 650-4* | P | B | FB | TB | MB | BL, SP, LR | 3.50 lbs. (1.6kg) |
| 650D-4 | P | B | FB | TB | MB | BL, SP, LR | 3.50 lbs. (1.6kg) |
| 650-58* | P | B,S | FB | TB | MB | BL, SP, LR | 4.10 lbs. (1.9kg) |
| 650-7* | P | B,S | FB | MB | MB | BL, SP, LR | 3.50 lbs. (1.6kg) |
| 650-77* | P | B,S | FB | TB | MB | BL,SP,LR,BP,RB | 5.00 lbs. (2.3kg) |
| 650-78* | P | B,S | FB | MB | MB | BL,SP,LR,BP,RB | 5.50 lbs. (2.5kg) |

* Optional Front D-Ring



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.