

Miller YR Series Safety Straps

Models: 6YRLS/6FTBR, 7YRLS/7FTBR

Description

Miller brand safety straps are equipped with locking snap hooks and are constructed with a red inner core/wear indicator. Should the red core become exposed, the strap must be removed from service. The YR Series safety strap is manufactured with six-ply nylon and remains flexible in all types of weather conditions. Tongue buckle adjuster included for quick, safe adjustment.



Materials

Webbing:	1 3/4" 6-Ply Neoprene
Hardware:	Steel
Rivets:	Copper
Label:	Metal Tag

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max. Working Load:	400 lbs (181.4kg)
Webbing Min.	
Tensile:	5,000 lbs (22kN)
Snaps:	5,000 lbs (22kN)
Buckle Min. Tensile:	4,000 lbs (18kN)

Certification

OSHA 1926.159, 1926.959, 1926.502 (d),
ANSI A10.32 and CSA Z259.11



by Honeywell

Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.