

REVOLUTION ARC-RATED HARNESS

TECHNICAL DATA

SP371 Rev. B

Nov 2020

Custom safety features have been incorporated for the security and protection of utility and maintenance workers. Arc-Rated harnesses are made with Kevlar/Nomex webbing, Kevlar web loop and rescue loops and leather insulators under all hardware.

MATERIALS

Webbing:	Kevlar/Nomex
Elastic Keepers:	Kevlar, Elastic
Thread (Stitching):	Kevlar, Polyester
Web Loop:	Kevlar
Rescue Loops:	Kevlar
Insulators:	Leather
Buckles:	Clear Chromate Finished Carbon Steel
Grommets:	Brass
Labels:	Valeron
Cam Buckle:	Glass-filled Nylon, Aluminum, Stainless Steel
Pivotlink:	Clear Chromate Finished Carbon Steel, Stainless Steel
Back, Belt, Shoulder Pads:	Kevlar, Urethane
Label Pack:	Evoprene, Nylon



TECHNICAL

Max. Working Load:	400lb (181.4kg)
Webbing Min.Tensile:	7000lb (31kN)
D-ring Min. Tensile:	5000lb (22kN)
Buckle Min. Tensile:	4000lb (18kN)

CERTIFICATIONS

Meets stringent ASTM F887-20 Arc-Flash standards all OSHA, ANSI and CSA requirements.

Miller Revolution Arc-Rated Harness with Kevlar/Nomex Webbing, Kevlar Web Loop and Leather Insulators under all hardware

MODEL	SIZE	STANDARD FEATURES	SIDE D-RINGS & PAD	LEG STRAP BUCKLES	RESCUE LOOPS	SPECIAL FEATURES
RKNAR-QR/UBK	U	Quick Connect Chest Buckles	No	Quick-Connect	No	Leather insulators, web back D-Ring
RKNAR-TB/UBK	U	Cam Buckles	No	Tongue	No	Leather insulators, web back D-Ring
RKNAR-QC-BDP/UBK	U	ErgoArmor Back Shield	Yes	Quick-Connect	No	Leather insulators, web back D-Ring, removable belt, side D-Rings & pad
RKNAR-TB-BDP/UBK	U		Yes	Tongue	No	Leather insulators, web back D-Ring, removable belt, side D-Rings & pad
RKNARRL-QC/UBK	U	Serl-contained Label Pack	No	Quick-Connect	Yes	Leather insulators, web back D-Ring
RKNARRL-TB/UBK	U		No	Tongue	Yes	Leather insulators, web back D-Ring
RKNARRL-QC-BDP/UBK	U	Web Finials	Yes	Quick-Connect	Yes	Leather insulators, web back D-Ring, removable belt, side D-Rings & pad
RKNARRL-TB-BDP/UBK	U		Yes	Tongue	Yes	Leather insulators, web back D-Ring, removable belt, side D-Rings & pad

For front D-ring vest-style option, add "FD" to the corresponding harness model number (Ex. RKNFD-QC/U)

Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Safety Products

9680 Old Bailes Road
Fort Mill, SC 29707

USA
Phone: 800.430.5490
Fax: 800.322.1330

⚠ This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality

Canada
Phone: 888.212.7233
Fax: 888.667.8477

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell