

CSA Certified StretchStop Lanyards with SofStop Energy Absorber

Description

Miller StretchStop Lanyards combine the integral SofStop® Shock Absorber with a unique stretchable lanyard design to reducing tripping hazards.

Materials

Webbing:

- Safety Strap: Type 7 webbing
- Safety Jacket: Tubular polyester

Thread: Polyester

SofStop Cover: Vinyl

Hardware: Steel

Locking Snap Hooks: 5,000 lb. (22kN)

All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

Non CSA Approved

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)

Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 1/2 in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and elongation distances.

Certification

Meets all CSA Z259.11-17 requirements.



M2FSFS-TS6C

CSA Certified StretchStop Lanyards with SofStop Energy Absorber

| Model Number | Color | Number of Legs | Harness Connection | Anchorage Connection | Lanyard Length |
|--------------|-------|----------------|--------------------|--------------------------|----------------|
| M1ASAR-TS6C | Green | One | Aluminum Snap Hook | Aluminum Rebar Hook | 6 ft. (1.8 m) |
| M1FSFC-TS6C | Green | One | Standard Snap Hook | Large Rebar Hook | 6 ft. (1.8 m) |
| M1FSFR-TS6C | Green | One | Standard Snap Hook | Standard Rebar (2") Hook | 6 ft. (1.8 m) |
| M1FSFS-TS6C | Green | One | Standard Snap Hook | Standard Snap Hook | 6 ft. (1.8 m) |
| M2ASAR-TS6C | Green | Two | Aluminum Snap Hook | Aluminum Rebar Hook | 6 ft. (1.8 m) |
| M2FSFC-TS6C | Green | Two | Standard Snap Hook | Large Rebar Hook | 6 ft. (1.8 m) |
| M2FSFS-TS6C | Green | Two | Standard Snap Hook | Standard Snap Hook | 6 ft. (1.8 m) |

Available lengths are only from 2.75ft (84cm) – 6 ft (1.8m). Locking Snap Hook – 3/4 in. (19 mm) gate opening; Locking Rebar Hook – 2-1/2 in. (64 mm) gate opening.

Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Industrial Safety


900 Douglas Pike
Smithfield, RI 02917

USA

Phone: 800.430.5490
Fax: 800.322.1330

Canada

Phone: 888.212.7233
Fax: 888.667.8477

 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.