

# MILLER™ MIGHTYLITE™+

Serious safety performance and legendary dependability are now part of the PLUS family of newly redesigned self-retracting lifelines, OSHA-rated to provide protection for up to a 420lb (190.5 kg) worker, showcasing new user-friendly labels and design that aligns with Honeywell Miller harnesses.

Ideal for a full range of applications, MightyLite+ self-retracting lifelines are available with galvanized wire rope. MightyLite+ lifelines are easy to carry and install overhead or may be permanently mounted for repeat use.

## 1. INCREASED WEIGHT RATING

- Increased weight rating up to 420lbs (190.5kg) - OSHA
- Meets requirements of OSHA, ANSI Z359.14 the new ANSI Z359.14-2021 Class 1, CSA Z259.2.2-2017

## 2. VARIETY OF LENGTHS

- Available in 20 ft, 30 ft, 50 ft, 100 ft & 130 ft options

## 3. UNIT & LANYARD CONNECTIONS

- Corrosion-resistant stainless steel and aluminum housing extend service life
- Integral swivel reduces lifeline twisting
- Narrow payout port limits intrusion of foreign debris
- Quick-activating inertia brakes limit a free fall to less than two feet
- No annual factory recertification required

## 4. REDESIGNED LABELS

- Enhanced graphics, icons, and colors on UV-resistant scratch-resistant labeling
- New Miller look and feel, designs aligned with Honeywell Harnesses for mix & match protection
- Labeling aids user with regular inspection by providing space for recording

## 5. LIFELINE

- Available in galvanized steel
- \* Stainless steel and Kevlar rope option coming soon
- Carabiner and tagline included



## ORDERING INFORMATION:

| SKU               | LENGTH | LIFELINE MATERIAL | UNIT CONNECTOR | LIFELINE CONNECTOR              | WEIGHT              | MAX WORKING CAPACITY |                      |
|-------------------|--------|-------------------|----------------|---------------------------------|---------------------|----------------------|----------------------|
|                   |        |                   |                |                                 |                     | ANSI/CSA             | OSHA                 |
| MML-OGC1-02/20FT  | 20 ft  | Galvanized Steel  | Carabiner      | Swivel Load Indicator Snap Hook | 11.5 lb<br>(5.2 kg) | 310 lb<br>(141 kg)   | 420 lb<br>(190.5 kg) |
| MML-OGC1-02/30FT  | 30 ft  | Galvanized Steel  | Carabiner      | Swivel Load Indicator Snap Hook | 13.8 lb<br>(6.2 kg) | 310 lb<br>(141 kg)   | 420 lb<br>(190.5 kg) |
| MML-OGC1-02/50FT  | 50 ft  | Galvanized Steel  | Carabiner      | Swivel Load Indicator Snap Hook | 28 lb<br>(12.7 kg)  | 310 lb<br>(141 kg)   | 420 lb<br>(190.5 kg) |
| MML-OGC1-02/100FT | 100 ft | Galvanized Steel  | Carabiner      | Swivel Load Indicator Snap Hook | 50 lb<br>(22.6 lb)  | 310 lb<br>(141 kg)   | 420 lb<br>(190.5 kg) |
| MML-OGC1-02/130FT | 130 ft | Galvanized Steel  | Carabiner      | Swivel Load Indicator Snap Hook | 64 lb<br>(29 kg)    | 310 lb<br>(141 kg)   | 420 lb<br>(190.5 kg) |

### For more information

[sps.honeywell.com](https://sps.honeywell.com)

Honeywell Safety Products USA, Inc.

855 S Mint St  
Charlotte, NC 28202  
[www.honeywell.com](https://www.honeywell.com)

HPPE Honeywell Miller Mighty Lite | US&C Sell Sheet | 07/23  
© 2023 Honeywell International Inc.

