

Fire Sentry FS10-R SPECIFICATIONS



Multi-Spectral Electro-Optical “Unitized” Flame Detector

General Specifications	
Sensitivity	45 ft. and 30 ft. to a 1 sq. ft. gasoline fire*
Response Time	Alert: 0.3 second (response to “fireball” type fires) Fire Early Warning: 1 second (early response to a fire alarm) Fire Alarm: Less than 5 seconds (if fire continues)
Field of View	90° (± 45° horizontal and vertical)
Spectral Sensitivity	Visible: 400 – 700 nanometers Near Band IR: 0.7 – 1.1 microns Wide Band IR: 0.7 – 3.5 microns
Input Power	24 VDC nominal (18-32 VDC) - Regulated
Power Consumption	Normal: 85 mA (typical); Alarm: 120 mA (typical)
Output Relays	Alert/Early Warning: SPST, N.O.* Fire Alarm: SPST, N.O. Fault: SPST, N.O. with no power Contact ratings: 1 amp @ 24 VDC
Normal Operation	Fault relay is Energized, Non-Latching All other relays are De-energized Fire and Alert relays are available Latching or Non-Latching
Operating Temperature	Operating: -40° to +185°F (-40° to +85°C)
Humidity Range	10% to 90% relative humidity, non-condensing
Weight	Aluminum: 3.8 lbs (1.7 kg)
Enclosure	Copper-Free Powder Coated Aluminum or optional 316 Stainless Steel; NEMA 3, 4 and 4X
Conduit Entries	Two ¾” NPT
Certifications	Explosion-Proof; Class I, Div. 1 & 2, Groups B, C, & D Class II, Div. 1 & 2, Groups E, F, & G Class III FM, CE
Dimensions	4.81 in. diameter; 4.65 in. deep
Mounting	Swivel Bracket Assembly - Optional
Warranty	Two years from date of shipping

* Detectors set at the 45-foot sensitivity setting do not have the Alert/Fire Early Warning output available.

Find out more

www.honeywellanalytics.com

Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.