## **Single Direction Bumper Receiver**

Model: DH-17

## Description\_

The Single Direction Bumper Receiver can be bolted or welded directly to a service vehicle to facilitate easier entry to a confined space, making use of the DH-12 vehicle hitch mount system.

#### Materials\_

General Construction: Welded Steel

Weld Certification:

AWS

Finish:

Zinc Plated

Hardware:

Gr. 5 Zinc Plated

**Plating Specification:** 

ASTM Designation

B633-85, Type II, SC2

### Technical\_

Working Load:

450lbs (204kg)

**Design Factor:** 

Dependent on other system


components, minimum 4:1

**Design Factor** 

Weight:

7.6lbs (3.4kg)

# Application Restrictions\_\_\_



- 2. Only one extension at a time is to be used with a hitch mounting sleeve. Multiple hitch mount sleeve extensions are not to be used.
- 3. The standard Hitch Mount Sleeve is to be used with a maximum 30" (762mm) offset mast.
- **4.** Anchoring to an attendant vehicle may not be permitted within certain jurisdictions. Ensure that use of this equipment does not violate any regulations within your area.
- 5. The Single Direction Bumper Receiver must be served directly to vehicle, not between a Hitch Mount Extension and Hitch Mount Sleeve.
- 6. Each installation must be approved to local standards by a qualified engineer.





▲ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

