

Non-Stretch Harness

8095 Series

Description

Non-Stretch harnesses are lightweight and available with a variety of attachments. Sizes available in small, medium, L, XL and XXL.

Materials

Webbing:	1-3/4 in. Polyester
Thread (Stitching):	6 cord bonded 3 strand polyester thread.
Hardware*	
D-Ring:	Clear Chromate Finished Carbon Steel
Buckles:	Clear Chromate Finished Carbon Steel
Grommets:	Brass
Labels:	Valeron
Label Pack:	Evoprene, Nylon

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Maximum Working Load Capacity

OSHA/CSA:	400 lbs. (181 kg)
ANSI:	310 lbs. (141 kg)

Hardware:	Steel Minimum Tensile strength
D-Ring	5000 lbs. (22kN)
Buckles	4000 lbs. (18kN)

Certification

Meets OSHA 1926.502, ANSI A10.32, Z359.1 and CSA requirements.



8095 shown

Model #	Shoulder Straps	Chest Straps	Leg Strap	Shoulder D-rings	Side D-rings	Special Features	Weight
8095	Friction	Mating	Friction	No	No	Attached Waist belt, Sub-Pelvic Strap, Lanyard Ring	4.0 lbs. (1.8 kg)
8095-3	Friction	Mating	Friction	Yes	No	Attached Waist belt, Sub-Pelvic Strap, Lanyard Ring	4.4 lbs. (2.0 kg)
8095-4	Friction	Mating	Tongue	No	No	Attached Waist belt, Sub-Pelvic Strap, Lanyard Ring	4.2 lbs. (1.9 kg)
8095-7	Friction	Mating	Friction	No	Yes	Attached Waist belt, Sub-Pelvic Strap, Lanyard Ring	4.7 lbs. (2.1 kg)



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.