# Miller Revolution<sup>™</sup> Vinyl-Coated Harnesses

## Description

Miller Revolution Vinyl Coated Harnesses feature a special vinyl coating on the webbing to protect against a variety of liquids that could compromise overall performance.

#### **Materials**

| Webbing:            | Vinyl-Coated                   |
|---------------------|--------------------------------|
| Elastic Keepers:    | Polyester, Nylon, Lycra        |
| Thread (Stitching): | Polyester                      |
| D-ring:             | Clear Chromate Finished Carbon |
|                     | Steel                          |
| Buckles:            | Clear Chromate Finished Carbon |
|                     | Steel                          |
| Grommets:           | Brass                          |
| Labels:             | Valeron                        |
| Pivotlink:          | Clear Chromate Finished Carbon |
|                     | Steel, Stainless Steel         |
| Label Pack:         | Evoprene, Nylon                |



#### Technical

| Max. Working Load:   | 400 lbs (181kg)  |
|----------------------|------------------|
| Webbing Min.Tensile: | 7,000 lbs (31kN) |
| D-ring Min. Tensile: | 5,000 lbs (22kN) |
| Buckle Min. Tensile: | 4,000 lbs (18kN) |

### Certification

Meets OSHA 1910.66, 1926.502, ANSI A10.32, Z359-2007 and CSA Z259.11 specifications.

| SKU           | Size      | Back<br>D-Ring | Front<br>D-Ring | Side<br>D-Rings | Chest<br>Strap<br>Buckle | Shoulder<br>Strap<br>Buckles | Leg<br>Strap<br>Buckles | Sub-<br>Pelvic<br>Strap | Weight             | Special<br>Features                    |
|---------------|-----------|----------------|-----------------|-----------------|--------------------------|------------------------------|-------------------------|-------------------------|--------------------|--|
| RPC-TB/UGN    | Universal | Yes            | Option          | No              | Mating                   | Friction                     | Tongue                  | Yes                     | 4.1 lbs<br>(1.9kg) | _                                      |
| RPC-TB-BD/UGN | Universal | Yes            | Option          | Yes             | Mating                   | Friction                     | Tongue                  | Yes                     | 5.3 lbs<br>(1.8kg) | Removable<br>belt with side<br>D-rings |

<u>Note:</u> For front D-ring vest-style option, add "FD" to the corresponding harness model number (Ex. RPC**FD**-TB/UGN). Model numbers listed are for universal size. Harnesses are also available in small/medium, XXlarge/XXXlarge, by replacing the "U" in the model number with "S/M" or "XXL/XXXL" (Ex. RPC-TB-BD/XXL/XXXLGN).



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.