

SofStop® MAX Shock-Absorbing Pack Options

Description

Miller SofStop® MAX Double Pack Lanyards combine the integral SofStop Shock Absorber.

Materials

Shock-Absorbing

Webbing: Polyester; 5,000 lb. min. tensile

Thread: 6 cord bonded 3 strand polyester thread; 42 lb. min. tensile

Hardware: Steel; min. tensile strength 5,000 lbs. (22kN)

- Locking Snap Hooks: 3/4 in. (19mm) gate opening
- Locking Rebar Hooks: 2 1/2 in. (63mm) gate opening
- Small Locking Rebar Hooks: 1 3/4 in. (45mm) gate opening
- Miller 5K Locking Snap Hook: 5/8 in. (16mm) gate opening

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Label Materials: Valeron

Certification

OSHA 1926.502, 1910.66; ANSI Z359.1, A10.32; CSA Z259.11 Class E6 (models with "E6" in part number)



940WLS/6FTGN



980WLS/6FTGN



940K/6FTBK

Technical

Standards	Maximum Allowable Free Fall	Minimum Capacity	Maximum Capacity	Maximum Arrest Force	Average Arrest Force	Maximum Elongation
ANSI A10.32	6 ft. (1.83m)	N/A	310 lbs. (140.6kg)	1800 lbs. (8kN)	N/A	3.5 ft. (1.1m)
ANSI Z359.13	6 ft. (1.83m)	130 lbs. (59kg)	310 lbs. (140.6kg)	1800 lbs. (8kN)	900 lbs. (4kN)	4 ft. (1.2m)
ANSI Z359.13 [For a 12 ft (3.66m) Free Fall]	12 ft. (3.66m)	130 lbs. (59kg)	310 lbs. (140.6kg)	1800 lbs. (8kN)	1350 lbs. (6kN)	5 ft. (1.5m)
CSA Z259.11 Class E6	6 ft. (1.83m)	200 lbs. (90kg)	386 lbs. (175kg)	1300 lbs. (6kN)	1250 lbs. (5kN)	5.7 ft. (1.75m)
OSHA 1926.502	6 ft. (1.83m)	130 lbs. (59kg)	400 lbs. (181kg)	1800 lbs. (8kN)	N/A	3.5 ft. (1.1m)

SofStop[®] MAX Shock-Absorbing Pack Options

Model Number	Webbing	Family	Harness Connection	Anchorage Connection
Single Legged Lanyards				
940B	Polyester	BackBiter [®]	ANSI Locking Snap Hook	Miller 5K [®] Locking Snap Hook
940B-E6	Polyester	BackBiter [®]	ANSI Locking Snap Hook	Miller 5K [®] Locking Snap Hook
940K	Kevlar/Nomex	Welding	Locking Snap Hook	Locking Snap Hook
940SS	Polyester	StretchStop [®]	Locking Snap Hook	Locking Snap Hook
940SS-E6	Polyester	StretchStop [®]	Locking Snap Hook	Locking Snap Hook
940WLS-Z7	Polyester	Shock-Absorbing	ANSI Locking Snap Hook	ANSI Locking Snap Hook
940WLS	Polyester	Shock-Absorbing	Locking Snap Hook	Locking Snap Hook
940NLS	Cable	Shock-Absorbing	Locking Snap Hook	Locking Snap Hook
940T-E6	Polyester	High Performance (HP)	Locking Snap Hook	Locking Snap Hook
Double Legged Lanyards				
980B	Polyester	BackBiter [®]	ANSI Locking Snap Hook	Two Miller 5K [®] Locking Snap Hooks
980B-E6	Polyester	BackBiter [®]	ANSI Locking Snap Hook	Two Miller 5K [®] Locking Snap Hooks
980K	Kevlar/Nomex	Welding	Locking Snap Hook	Two Locking Snap Hooks
980SS	Polyester	StretchStop [®]	Locking Snap Hook	Two Locking Snap Hooks
980SS-E6	Polyester	StretchStop [®]	Locking Snap Hook	Two Locking Snap Hooks
980WLS-Z7	Polyester	Shock-Absorbing	ANSI Locking Snap Hook	Two ANSI Locking Snap Hooks
980WLS	Polyester	Shock-Absorbing	Locking Snap Hook	Two Locking Snap Hooks
980T-E6	Polyester	High Performance (HP)	Locking Snap Hook	Two Locking Snap Hooks

NOTE: Additional models available upon request, including small & large Locking Rebar Hook connections.



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

⚠ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.