

# Miller Horizontal Lifeline Cross-Arm Strap

Models: HLLCS/6FT, HLLCS/10FT, HLLCS/20FT, HLLCS/30FT

## Description

The Horizontal Lifeline Cross-Arm Strap wraps around I-beams and other structures by slipping a 4-inch (102 mm) D-ring through a 6" web loop to form a secure attachment point for lanyards and other connecting devices.

## Materials

**Webbing:** 3-in (76 mm) Polyester webbing

**D-Ring:** Steel; 4-in (102 mm) diameter

**Thread:** Six-cord bonded three-strand polyester thread.

**Labels:** Valeron

\*All hardware meets ASTM (50) fifty-hour salt spray test requirements

## Technical

### Maximum Working

**Load Capacity:** 400 lbs (181.4 kg)

**Webbing:** 5,000 lbs (22 kN) minimum tensile strength

**D-Ring:** 5,000 lbs (22 kN) minimum tensile strength

**Thread:** 42 lbs (19 kg) minimum tensile strength

**Length:** 10 ft (3 m) standard length  
[Available in 6 ft (2m), 10 ft (3m), 20 ft (6m) and 30 ft (9m)]

## Certification

OSHA 1926.502, OSHA 1910.66, ANSI A10.32 and ANSI Z359-2007



# MILLER®

by Honeywell

Toll Free 800.873.5242 (press 4) • [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com) • [www.millerfallprotection.com](http://www.millerfallprotection.com)

**⚠ WARNING!** THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.