

CSA Certified HP™ Lanyards with SofStop® Energy Absorber

Description

The Miller HP Lanyards are a collection of the most popular standard Miller brand lanyards with SofStop Energy Absorbers. The SofStop® Energy Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces.

Materials

Webbing: Polyester

SofStop Shock Absorber

- Webbing: Polyester

- Safety Strap

(Inside SofStop): Polyester

Locking Snap

Hook: Steel, ¾ in. (19 mm) gate opening

Miller 5K Locking

Snap Hook: Steel, ¾ in. (19 mm) gate opening

Thread: Polyester

All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

Non CSA Approved

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)

Snap Hooks: 5,000 lbs. (22kN)

¾" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 ½ in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and elongation distances.

Certification

Meets all CSA Z259.11-17 requirements.



M1FSFC-WS6C

CSA Certified HP™ Lanyards with SofStop® Energy Absorber

Model Number	Color	Number of Legs	Harness Connection	Anchorage Connection	Standard Length
M1ASAS-WS6C	Green	One	Aluminum Snap Hook	Aluminum Snap Hook	6 ft. (1.8 m)
M1FSCA-WS4C	Green	One	Standard Snap Hook	Carabiner	4 ft (1.2 m)
M1FSFC-WS6C	Green	One	Standard Snap Hook	Large Rebar Hook	6 ft. (1.8 m)
M1FSFR-WS6C	Green	One	Standard Snap Hook	Standard Rebar (2")	6 ft. (1.8 m)
M1FSFS-WS6C	Green	One	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)
M1FSFS-WS46C	Green	One	Standard Snap Hook	Standard Snap Hook	Adj.
M1FSFS-YS4C	Yellow	One	Standard Snap Hook	Standard Snap Hook	4 ft (1.2 m)
M1WLFS-WS4C	Green	One	Web Loop	Standard Snap Hook	4 ft (1.2 m)
M2ASAR-WS6C	Green	Two	Aluminum Snap Hook	Aluminum Rebar Hook	6 ft. (1.8 m)
M2FSFC-WS6C	Green	Two	Standard Snap Hook	Large Rebar Hook	6 ft. (1.8 m)
M2FSFR-WS6C	Green	Two	Standard Snap Hook	Standard Rebar (2")	6 ft. (1.8 m)
M2FSFS-WS6C	Green	Two	Standard Snap Hook	Standard Snap Hook	6 ft. (1.8 m)

Locking Snap Hook – 3/4 in. (19 mm) gate opening; Locking Rebar Hook – 2 1/2-in. (64 mm) gate opening. Aluminum models available upon request. All connectors include 3,600-lb. gate-strength.

Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Industrial Safety


900 Douglas Pike
Smithfield, RI 02917

USA

Phone: 800.430.5490
Fax: 800.322.1330

Canada

Phone: 888.212.7233
Fax: 888.667.8477

 This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.