

Now Available
In Stainless Steel Components


Miller
SkyGRIP™
Permanent Horizontal Lifeline System

The new Miller SkyGrip™ Stainless Steel Permanent Horizontal Lifeline System Kits are designed for quick, easy installation in corrosive environments. A variety of innovative features have been engineered into these new systems, making them extremely user friendly with enhanced safety considerations.

- **100% stainless steel construction** - corrosion resistant stainless steel components for a longer service life.
- **Ideal for corrosive environments** - designed for petrochemical, pharmaceutical, food processing, outdoor and off-shore applications.
- **Engineered and safety tested by experts** in the industry that understand fall forces & system design.
- **Compact & lightweight** - provides for easier handling and installation.
- **Single-span systems** - spans adjust up to 60-ft (18.3m) & accommodate up to two workers.
- **Stainless steel tension indicator** - proper tensioning of system ensures accurate fall clearance requirements.
- **Compact, stainless steel Miller SkyGrip energy absorber** - engineered to keep system forces consistently low during a fall and minimizes fall clearance.



SKU	Length	Description (Stainless Steel = SS)
SG416-FS/60FT	60FT	SS lifeline kit (SGLLK-FS/60FT); (2) 416SS/ D-bolt anchors
SG417-FS/60FT	60FT	SS lifeline kit (SGLLK-FS/60FT); (2) 417SS/ D-bolt anchors
SGLLK-FS/30FT	30FT	SS lifeline; (4) SS anchor shackles, turnbuckle, cable clamps, tension indicator, thimble & energy absorber
SGLLK-FS/60FT	60FT	SS lifeline; (4) SS anchor shackles, turnbuckle, cable clamps, tension indicator, thimble & energy absorber
SGXK-FS	N/A	SS energy absorber kit; SS tension indicator, (2) SS anchor shackles & SS hardware
416SS/	N/A	SS D-bolt anchor, 5/8-in. hole for hardware, 5/8-in. dia x 5-in long SS bolt w/nut & washer
417SS/	N/A	SS D-bolt anchor, 5/8-in. hole for hardware, does not include hardware



Model SG416-FS/60FT shown above



by Honeywell

▶ Ask the Expert ... Ask Miller.

800/873-5242
or 814/432-2118

Fax 800/892-4078
or Fax 814/432-2415

(Press 4 for Technical Service)

www.millerfallprotection.com