

Miller RA25-1/ Reusable Roof Anchor

The RA25-1/ temporary foldable roof anchor is used as part of a personal fall arrest system. It is designed for residential and commercial construction applications and comes complete with twelve (12) 2 1/2 in. #8 screws.

The RA25-1/ is intended for use on wood framed structures with pitches from 0-12/12. This allows for anchorage connection at the roof peak or in a flat position. The RA25-1/ may be secured with either 2 1/2 in. #8 screws or 16d nails.

Materials

Anchor / D-Ring: Red painted 1020 carbon steel
Screws: Flat head metal

Technical

Weight: 2.46 lbs. (1.12 kg)
Max. Working Load: 420 lbs. (190.51 kg)
[fall arrest system must limit force to 1,800 lbf (8kN)]

Certification

Meets OSHA1926.502 requirements



Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242

www.millerfallprotection.com

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI 02917

USA

Phone: 800.430.5490

Fax: 800.322.1330

Canada

Phone: 888.212.7233

Fax: 888.667.8477

⚠ WARNING! This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.