

# TRANSPORTABLE WIRELESS SOLUTIONS.


Have confidence in your local area monitoring

Honeywell BW™ RigRat

Honeywell




# HONEYWELL BW™ RIGRAT WIRELESS SYSTEM CONFIGURATIONS



## CLOSED-LOOP

- Mesh 868 MHz, 900 MHz or 2.4 GHz system
- Network hops: one alarmed, all alarmed
- Work mode: Router
- One Honeywell BW™ Rigrat can connect up to 8 Honeywell BW™ Rigrats
- Up to 16 units in one system
- Wireless distance on ground level: 984 ft. / 300 m (868-900 MHz) or 492 ft. / 150 m (2.4 GHz)
- Parallel network configuration means no detector is selected as a coordinator and thereby any detector can be taken out of the system without reconfiguration of the wireless network




## HONEYWELL BW™ RIGRAT + PORTABLE GAS MONITORS + CONTROLLER

- Mesh 915/868 MHz
- Network hops: 3
- Work mode: RTR (Router)
- Capacity: 64 points (56 STD + 8 RTR)
- Supports RAEPoint
- Supports MultiRAE – MultiRAE lite and MicroRAE
- Connects to Honeywell software
- Ideal for turnaround and rig operations




### HONEYWELL BW™ RIGRAT + MESHGUARD + CONTROLLER

- Mesh 2.4 GHz
- Network hops: 3
- Work mode: RTR (Router)
- Capacity: 64 points (56 STD + 8 RTR, decided by host)
- RAEPPoint remote
- Compatible with MeshGuard detectors
- EchoView will only display MeshGuard



### HONEYWELL BW™ RIGRAT + RADIANT READER

- Mesh 868/900 MHz
- Network hops: 10
- Work mode: RTR (Router)
- Capacity: 100STD+20RTR
- Wireless distance on ground level: > 984 ft. / 300 m LOS
- Location: GPS, 10 m @ 50%
- Compatible with Radiant Reader and Honeywell software



## HONEYWELL BW™ RIGRAT + WI-FI

- Wireless distance on ground level: 164 ft. / 50m LOS
- Location: GPS, 10 m
- Supports n/g Wi-Fi network
- Does not support authentication



## HONEYWELL BW™ RIGRAT + BLUETOOTH LOW ENERGY (BLE)

- All Honeywell BW™ Rigrat units are equipped with BLE
- Mobile app simplifies setup and configuration
- Less trained personnel can be dispatched to the unit to update configuration data
- Reduce training times to as low as 20 minutes
- All settings are configured via mobile app
- Email datalog file and calibration certificates via mobile app
- Easy calibration tracking

### For More Information

[www.honeywellanalytics.com](http://www.honeywellanalytics.com)

Brochure\_Honeywell BW Rigrat\_Wireless-Solutions\_DS061119\_00\_US-EN | 06/19  
 Note: Due to ongoing research and product improvement, specifications are subject to change without notice.  
 © 2019 Honeywell International Inc.

THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT

**Honeywell**