

Miller 213 Series - Positioning/Restraint

Description

The 213 non shock absorbing lanyards are to be used for positioning only, unless it is used in conjunction with a shock absorber. The standard web lanyards are economical, abrasion resistant and easy to clean.

Materials

Webbing: 1 in. (25.4 m) Polyester Webbing
Snap Hooks: Steel, 3/4 in. (19 mm) gate opening
Thread: Polyester
Labels: Lexan and Valeron

*All hardware meets ASTM (50) fifty-hour salt spray test requirements

Technical

Max. Working Load: 400 lbs. (181.4 kg)
 130-310 lbs. (When tested to ANSI Z359.1)

Minimum Tensile

- Lanyard Webbing: 5,000 lbs. (22 kN)
 - Snap Hook: 5,000 lbs. (22 kN)
 - Thread: 42 lbs. (0.18 kN)

Certification

Meets all OSHA 1910.66, 1926.502(d), ANSI A10.32, Z359.13 and CSA Z259.11 requirements.



| Model Number | Description | Standard Length* |
|------------------|--|------------------|
| 213WLS-Z7/6FTYL | Yellow web lanyard with two locking snap hooks | 6 ft. (1.8 m) |
| 213TWDLS/6FTBL | Blue web lanyard with two locking snap hooks | |
| 213TWLS-Z7/6FTGN | Green web lanyard with two locking snap hooks | |

*Additional Lengths are available

Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242
www.millerfallprotection.com

Honeywell Industrial Safety

900 Douglas Pike
 Smithfield, RI 02917

USA

Phone: 800.430.5490
 Fax: 800.322.1330

Canada

Phone: 888.212.7233
 Fax: 888.667.8477

⚠ This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.