

## Miller Rebar Positioning Assembly 6756RS-Z7

### Description

The Rebar Positioning Assembly comes with two locking snap hooks and one locking rebar hook, intermediate swivel, grade 80 chain, and includes a length adjuster.

### Materials

Hardware:	Steel, Zinc Plated
Label Materials:	Lexan and Valeron
Locking Snap Hooks:	3/4 in. (19 mm) gate opening
Rebar Snap Hooks:	2 1/2 in. (63.5 mm) gate opening

\*All hardware meets ASTM fifty-hour salt spray test requirements.

### Technical

Max. Working Load:	310 lbs. (140.63 kg)
Locking Snap Hooks:	5,000 lbs. (22 kN)
Locking Rebar Hooks:	5,000 lbs. (22 kN)

### Certification

Meets OSHA 1926.502 and ANSI A10.32 and Z359 requirements.



6756RS-Z7

**Warning!! This product is to be used for positioning only!**

**Limitless Possibilities. Ask the Expert.**  
Technical Service: 800.873.5242  
[www.millerfallprotection.com](http://www.millerfallprotection.com)

**Honeywell Industrial Safety**  
900 Douglas Pike  
Smithfield, RI 02917

**USA**  
Phone: 800.430.5490  
Fax: 800.322.1330

**Canada**  
Phone: 888.212.7233  
Fax: 888.667.8477

**!** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

## Fall Clearance Diagram

