

## CSA Certified Back Biter® Tie Back Lanyards

### Description

Miller BackBiter® Tie-Back Lanyards, with a Miller 5K® Snap Hook was designed for tie-back use. The all-in-one lanyard with SofStop® shock absorber and cross-arm anchorage connector reduces inventory and increases worker compliance.

### Materials

Webbing: Polyester or Kevlar

#### SofStop Shock Absorber

- Webbing: Polyester or Kevlar

- Safety Strap

(Inside SofStop): Polyester

Locking Snap

Hook: Steel, 3/4 in. (19 mm) gate opening

Miller 5K Locking

Snap Hook: Steel, 3/4 in. (19 mm) gate opening

Thread: Polyester

All hardware meets ASTM (50) fifty-hour salt spray test requirements.

### Technical

CSA Approved

Max. Capacity Range: 120-335 lbs. (141 kg)

Maximum Elongation

Distance: 52 in. (in a 6 ft. drop)

Non CSA Approved

Max. Capacity Range: 100-385 lbs. (175 kg)

Maximum Elongation

Distance: 68 in. (in a 6 ft. drop)

Snap Hooks: 5,000 lbs. (22kN)

3/4" (19mm) gate opening

Rebar Hooks: 5,000 lbs. (22kN)

2 1/2 in. (63mm) gate opening

Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and elongation distances.



M1FSTB-AS6C

### Certification

Meets all CSA Z259.11-17 requirements.

| Model Number | Material       | Color | Number of Legs | Harness Connection | Anchorage Connection | Lanyard Length |
|--------------|----------------|-------|----------------|--------------------|----------------------|----------------|
| M1FSTB-KS6C  | Kevlar webbing | Black | One            | Standard Snap Hook | Tie Back Snap Hook   | 6 ft. (1.8 m)  |
| M1FSTB-AS6C  | Tie Back       | Green | One            | Standard Snap Hook | Tie Back Snap Hook   | 6 ft. (1.8 m)  |
| M2FSTB-AS6C  | Tie Back       | Green | Two            | Standard Snap Hook | Tie Back Snap Hook   | 6 ft. (1.8 m)  |

Locking Snap Hook has a 3/4 in. (19 mm) gate opening. Cordura is a registered trademark of E. I. DuPont. All connectors include 3,600 lb. gate strength.

#### Limitless Possibilities. Ask the Expert.

Technical Service: 800.873.5242

www.millerfallprotection.com

#### Honeywell Industrial Safety

900 Douglas Pike  
Smithfield, RI 02917

#### USA

Phone: 800.430.5490

Fax: 800.322.1330

#### Canada

Phone: 888.212.7233

Fax: 888.667.8477

**⚠** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.