

Time to get serious... ...about safety!

by Honeywell



MiniLite[™] Fall Limiter

This award-winning scene stealer basks in the spotlight as the most compact and lightweight fall limiter on the market that offers up to 11 feet of working capacity. It fits in the palm of your hand and arrests free falls within inches.



Select from a variety of 5,000 lb. [22kN] rated anchorage connecting options for your MiniLite Fall Limiter. Integration of anchorage connection devices reduces overall cost of ownership.

















A Measurable Difference

- Weighs only 2.5 lbs. [1.1kg]
- Compact, hand-held design measures only 3-3/4"W x 3-1/4"D x 18"L [9.5cm x 8cm x 45.5cm] when fully retracted
- 11 feet [3.3m] of working capacity more than any other unit of its size on the market

Gravity-Defying Performance

 Quick-activating, high-strength stainless steel braking system arrests a free fall within inches



Applauded Service Life

- High-impact outer cover protects internal components from harsh environmental elements
- Stainless steel interior, frame and components are corrosion resistant
- Polyester webbing offers greater chemical resistance
- No annual factory recertification required

Unrivaled Safety Benefits

- Visual load indicator warns the user that the unit has been involved in a fall and should be removed from service
- Prominent reflective labeling provides high visibility for evening work activities
- Meets OSHA, ANSI, (SP Z259.2.2 Type 2 and **(** requirements for global compliance

Miller MiniLite Fall Limiter -Anchorage Connector Options

Model Number	Description	Occ	upati	ons/l	Jse	
FL11	MiniLite without an anchorage connector	U				
FL11-1	MiniLite w/steel twist-lock carabiner	7	~	M	Ĩ.	ij.
FL11-2	MiniLite w/stainless steel swivel shackle	1	~	M	<u> </u>	ij ª
FL11-3	MiniLite w/carabiner & swivel shackle	U				
FL11-4	MiniLite w/attached 3' [1m] cross-arm strap*	1	M	1	Ĩ.	
FL11-5	MiniLite w/locking rebar hook (2-1/2" [63mm] gate opening)	7	M	1	<u></u>	幽
FL11-6	MiniLite w/rebar hook & swivel shackle	7	M	-8	Ĩ.	緻
FL11-7	MiniLite w/locking snap hook (3/4" [19mm] gate opening)	U				
FL11-8	MiniLite w/snap hook & swivel shackle	U				
FL11-9	MiniLite (FL11) w/no snap hook on the web lanyard end	U				
FL11-10	MiniLite w/swivel shackle (FL11-2) & no snap hook on the web lanyard end	U				

^{*}Additional lengths available.

MightyLite Self-Retracting Lifelines

Lightweight, heavy-duty MightyLite Self-Retracting Lifelines easily beat the competition on the applause meter.

A Class Act Design

- Up to 30% lighter than competitive models in their class...and more compact
- Double-swivel design allows for greater maneuverability while preventing the lifeline from twisting or kinking





- Consistent spring tension regardless of the amount of wire rope or webbing in use
- Steel twist-lock carabiner and tagline included for attaching to an anchorage

Legendary Dependability

 No annual factory recertification required* – keeping the units on the job for increased productivity and lower overall cost of ownership

- Corrosion-resistant stainless steel and aluminum components promote longer service life
- Narrow payout port prevents intrusion of foreign debris



Serious Safety Performance

- Quick-activating inertia brakes limit a free fall to less than two feet
- Integral load indicator appears red when the unit has been involved in a fall
- Labeling aids user with regular inspection by providing space for recording
- Meets OSHA, ANSI, ♠ Z259.2.2 Type 2 and ♠ requirements for global compliance

Occupation/Use Legend



Construction



ROOFING



SCAFFOLD



IRONWORKER



INDUSTRIAL



WAREHOUSE



PAINTER



Positioning/Restraint



UTILITY



Universal



TELECOMMUNICATIONS

No Annual Factory Recertification Required*

*Does not apply to Canada due to CSA Z259.2.2-98 requirements. For all units sold, end-user visual and functional inspections should still be performed on a regular basis. If, based on inspection criteria, a MightyLite unit is found to require service, Miller Fall Protection has a complete service and repair program in place to assist end-users.

Model Number	Lifeline Material	Length	Weight	Occupations Use
RL20P	1" (25mm) Polyester webbing	20' (6m)	8 lbs. (3.6kg)	U
RL20G	3/16" (5mm) Galvanized wire rope	20' (6m)	9 lbs. (4kg)	U
RL20SS	3/16" (5mm) Stainless steel wire rope	20' (6m)	9 lbs. (4kg)	U
RLS30G	3/16" (5mm) Galvanized wire rope	30' (10m)	10.9 lbs. (4.9kg	
RLS30S	3/16" (5mm) Stainless steel wire rope	30' (10m)	10.9 lbs. (4.9kg	
RL50P	1" (25mm) Polyester webbing	50' (15m)	19 lbs. (8.6kg)	U
RL50G	3/16" (5mm) Galvanized wire rope	50' (15m)	21 lbs. (9.5kg)	U
RL50SS	3/16" (5mm) Stainless steel wire rope	50' (15m)	21 lbs. (9.5kg)	U
RL65G	3/16" (5mm) Galvanized wire rope	65' (20m)	30 lbs. (13.6kg) U
RL65SS	3/16" (5mm) Stainless steel wire rope	65' (20m)	30 lbs. (13.6kg	U
RL100G	3/16" (5mm) Galvanized wire rope	100' (30m)	40 lbs. (18.1kg	
RL100SS	3/16" (5mm) Stainless steel wire rope	100' (30m)	40 lbs. (18.1kg	
RL130G	3/16" (5mm) Galvanized wire rope	130' (40m)	50 lbs. (22.7kg	
RL130SS	3/16" (5mm) Stainless steel wire rope	130' (40m)	50 lbs. (22.7kg) U

Charles Chaplin and The Little Tramp are trademarks and/or servicemarks of Bubbles, Inc. S.A. Used with permission.



Fall Limiter Debuts to Rave Reviews

First introduced to audiences in 1999, the MiniLite Fall Limiter was clearly a rising star – a self-retracting lanyard with a quick-activating braking system that limits a free fall to inches. In contrast to shock-absorbing lanyards, the fall limiter eliminates the need for extended fall distance clearance. This minimizes the risk of injuries and makes rescue easier.

In its debut on the fall protection scene, MiniLite received several safety awards and continues to play a leading role.

Arrests Free Falls Within Inches



Self-Retracting Lifelines Offer a Full Reel of Versatility

These performers go to any length to display versatility. Ideal for a full range of applications, MightyLite Self-Retracting Lifelines are available with galvanized wire rope, stainless steel wire rope, Kevlar® rope and/or polyester webbing in lengths from 20 feet [6m] to 130 feet [40m].

Up to 30 percent lighter than competitive models in their class, MightyLite Lifelines are easy to carry and install overhead or may be permanently mounted for repeat use – the perfect fall protection solution. And, with no annual factory recertification required, they remain on-the-job maximizing productivity.

No Annual Factory Recertification Required



Presenting: A Fall Protection Ensemble

We have seasoned performers waiting in the wings to fill any role in your fall protection program. With stars like DuraFlex® Stretchable Harnesses, BackBiter Tie-Back Lanyards and Manyard II Shock-Absorbing Lanyards, you can look forward to encores on just about any set.

Miller DuraFlex Stretchable Harnesses

Patented Miller DuraFlex Harnesses feature speciallyformulated elastomer webbing that stretches:

Greater Comfort

DuraFlex Harnesses conform to the shape of the worker, stretching with every movement, so there is no bunching, binding or kinking.

Improves Safety

With comfort unsurpassed, DuraFlex Harnesses offer wider end-user acceptance. And, a comfortable harness is worn properly, enhancing compliance and safety on the jobsite.

Increases Productivity

Because DuraFlex Harnesses are stretchable, the worker has greater mobility with less fatigue.

Miller® BackBiter™ Tie-Back Lanyard

• All-in-one lanyard with SofStop® Shock Absorber and cross-arm anchorage connector with the only 5K™ Snap Hook able to withstand a 5,000 lb. gate load capacity from any angle.

Miller® Manyard® II Shock-Absorbing Lanyard

• Innovative stretchable webbing design offers greater maneuverability and safety while minimizing potential tripping hazards.

Miller® Training ToolBox™

 A comprehensive training kit designed for safety professionals responsible for fall prevention and protection training.

For additional MiniLite and MightyLite product and ordering information, call Miller Customer Service to request your FREE full-color, 40-page "Gravity Kills...Defy It!" catalog.

Charles Chaplin and The Little Tramp are trademarks and/or servicemarks of Bubbles, Inc. S.A. Used with permission.

This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.



by Honeywell

Ask the Expert ... Ask Miller.

800/873-5242 or 8|4/432-2||8

Fax 800/892-4078 or Fax 814/432-2415

шшш.millerfallprotection.com

For more information or to place an order, please contact your Miller® distributor:

LSRL/0900/20M/HP