


New!

Miller® Contractor Harness

Specifically designed for use in construction


- Lightweight for greater comfort; non-stretch webbing
- Unique combination back D-ring pad/ shoulder pads that minimize discomfort/stress around the neck and shoulders when using a tool belt
- Soft lumbar back pad for additional support and comfort
- Waist belt (removable) to accommodate tool pouches
- Single, back D-ring for fall protection
- Tongue buckle leg straps for easy adjustment
- Friction buckle shoulder adjustments; mating buckle chest adjustment
- Self-contained label pack positioned for easy access
- Two (2) pull-free lanyard rings
- Rated to 400 lbs. (181.4 kg) capacity
- Meets applicable OSHA, ANSI and CSA Standards



Tongue buckle leg straps



Self-contained label pack



Two (2) pull-free lanyard rings

| SKU | Size | Back D-Ring | Front D-Ring | Side D-Rings | Chest Strap Buckle | Shoulder Strap Buckles | Leg Strap Buckles | Sub-Pelvic Strap | Special Features |
|-----------------|-------------------|-------------|--------------|--------------|--------------------|------------------------|-------------------|------------------|--|
| 650CN-BP/UGN | Universal (L, XL) | Yes | Option | No | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops |
| 650CN-BP/S/MGN | Small/Medium | Yes | Option | No | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops |
| 650CN-BP/XXLGN | XXL | Yes | Option | No | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops |
| 650CN-BDP/UGN | Universal (L, XL) | Yes | Option | Yes | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops |
| 650CN-BDP/S/MGN | Small/Medium | Yes | Option | Yes | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops |
| 650CN-BDP/XXLGN | XXL | Yes | Option | Yes | Mating | Friction | Tongue | Yes | D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops |

This equipment should only be used in conjunction with the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.



by Honeywell

Ask the Expert ... Ask Miller.

800/873-5242
or 814/432-2118

Fax 800/892-4078
or Fax 814/432-2415

www.millerfallprotection.com

For more information or to place an order, please contact your Miller® distributor:

LMCH/0308/15M/RPI