

# MultiRAE Lite

## Wireless Portable Multi-Gas Monitor

The MultiRAE Lite is the optimal one-to-six<sup>1</sup>-gas monitor for personal protection and leak detection applications. The MultiRAE Lite is available in pumped and diffusion versions and features the broadest selection of sensor options in its class. The MultiRAE Lite can be configured to exactly meet the detection needs and compliance requirements of various countries, industries, and applications.

The MultiRAE Lite's optional wireless capability improves safety by providing commanders and safety officers real-time access to instrument readings and alarm status from any location for better situational awareness and faster incident response.



Confined space testing with the MultiRAE Lite

### APPLICATIONS

- Personal protection and multi-gas leak detection in industries such as:
  - Chemical
  - Food and beverage
  - Oil and gas (downstream)
  - Pharmaceutical
  - Telecommunications
  - Wastewater treatment
- Fire overhaul

- Available in pumped and diffusion versions
- Highly versatile and customizable
- Man Down Alarm with real-time remote wireless notification
- Easy maintenance with replaceable sensors, pump, and plug-and-play battery
- Fully automatic bump testing and calibration with AutoRAE 2

## FEATURES & BENEFITS

- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions including Man Down Alarm<sup>2</sup>
- Over 25 interchangeable sensor options, including PID<sup>4</sup> for VOCs, NDIR5 and catalytic for combustibles, and NDIR for CO<sub>2</sub>
- Intelligent sensors store calibration data, so they can be swapped in the field<sup>6</sup>
- Large graphical display with easy-to-use, icon-driven user interface
- Continuous datalogging (6 months for 5 sensors, 24x7)
- Device Management with Honeywell SafetySuite

# MultiRAE Lite Specifications

| INSTRUMENT SPECIFICATIONS <sup>7</sup>                  |   |
|---|---|
| SIZE  | - Pumped model: 7.6" H x 3.8" W x 2.6" D (193 x 96.5 x 66 mm)<br>- Diffusion model: 6.9" x 3.8" x 2.2" (175 x 96.5 x 56 mm)   |
| WEIGHT  | - Pumped model: 31 oz (880 g) - Diffusion model: 26.8 oz (760g)   |
| SENSORS   | Over 25 intelligent interchangeable field-replaceable sensors including PID for VOCs, electrochemical sensors for toxic gases and oxygen, combustible LEL and NDIR sensors, and CO <sub>2</sub> NDIR sensor   |
| BATTERY OPTIONS, RUNTIME <sup>8</sup> AND RECHARGE TIME | - Rechargeable Li-ion ~12-hr. (pumped)/18-hr. (diffusion) runtime, < 6-hr. recharge time<br>- Extended duration Li-ion ~18-hr. (pumped)/28-hr. (diffusion) runtime, < 9-hr. recharge time<br>- Alkaline adapter with 4 x AA batteries ~6-hr. (pumped)/8-hr. (diffusion) runtime   |
| DISPLAY   | Monochrome graphical LCD display (128 x 160) with backlighting, Automatic screen "flip" feature<br>- Real-time reading of gas concentrations; PID measurement gas and correction factor; Man Down Alarm on/off; visual compliance indicator; battery status; datalogging on/off; wireless on/off and reception quality.   |
| DISPLAY READOUT   | -STEL, TWA, peak, and minimum values  |
| KEYPAD BUTTONS  | Automatic with AutoRAE 2 Test and Calibration System <sup>3</sup> or manual   |
| SAMPLING  | Built-in pump or diffusion  |
| CALIBRATION   | Automatic with AutoRAE 2 Test and Calibration System or manual  |
| ALARMS  | Wireless remote alarm notification; audible (95 dB @ 30 cm), vibration, visible (flashing bright red LEDs), and on-screen indication of alarm conditions<br>- Man Down Alarm with pre-alarm and real-time remote wireless notification <sup>2</sup>   |
| DATALOGGING   | Continuous datalogging (6 months for 5 sensors at 1-minute intervals, 24/7)<br>- User-configurable datalogging intervals (from 1 to 3,600 seconds)  |
| COMMUNICATION AND DATA DOWNLOAD                         | - Data download and instrument set-up and upgrades on PC via desktop charging and PC comm. cradle, travel charger, or AutoRAE 2 Automatic Test and Calibration System <sup>3</sup><br>- Wireless data and alarm status transmission via built-in RF modem (optional)  |
| WIRELESS NETWORK  | ProRAE Guardian Real-Time Wireless Safety System or EchoView Host-based Closed-Loop System  |
| WIRELESS RANGE (TYPICAL)                                | MultiRAE Lite to RAELink3 [Z1] Mesh modem ~330 feet (100 meters)<br>MultiRAE Lite to EchoView Host, RAEMesh Reader or RAEPoint ~660 feet (200 meters)<br>MultiRAE Lite to Wi-Fi Access Point - 330 feet (100 meters)  |
| OPERATING TEMPERATURE                                   | -4° to 122°F (-20° to 50°C)   |
| HUMIDITY  | 0% to 95% relative humidity (non-condensing)  |
| DUST AND WATER RESISTANCE                               | IP-65 (pumped); IP-67 (diffusion) ingress protection rating   |
| SAFETY CERTIFICATIONS                                   | CSA: Class I, Division 1, Groups A, B, C and D, T4<br>Class II, Division 1, Groups E, F, G T85°C<br>ATEX: 0575 II 1G Ex ia IIC T4 Ga<br>2G Ex ia d IIC T4 Gb with IR Sensor installed<br>I M1 Ex ia I Ma<br>IECEX: Ex ia IIC T4 Ga<br>Ex ia d IIC T4 Gb with IR Sensor installed<br>I M1 Ex ia I Ma<br>IECEX/ANZEx: Ex ia IIC T4 Ga<br>Ex ia d IIC T4 Gb with IR Sensor installed<br>Ex ia I Ma |
| EMC/RFI <sup>8</sup>                                    | EMC directive: 2004/108/EC  |
| PERFORMANCE TESTS                                       | LEL CSA C22.2 No. 152; ISA-12.13.01   |
| LANGUAGES   | Arabic, Chinese, Czech, Danish, Dutch, English, French, German, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, and Turkish<br>- Four years on Liq O <sub>2</sub> sensors  |
| WARRANTY  | - Three years on CO and H <sub>2</sub> S sensors<br>- Two years on non-consumable components and catalytic LEL sensors<br>- One year on all other sensors, pump, battery, and other consumable parts  |
| WIRELESS FREQUENCY                                      | ISM license free band. IEEE 802.15.4 Sub 1GHz - Wi-Fi 802.11 b/g  |
| WIRELESS APPROVALS                                      | FCC Part 15, CE R&TTE, Others <sup>10</sup>   |
| RADIO MODULE  | Supports RM900A   |

| SENSOR SPECIFICATIONS <sup>7</sup>                           | RANGE           | RESOLUTION |
|--|-----------------|------------|
| PID SENSORS <sup>4</sup>                                     |                 |            |
| VOC 10.6 EV  | 0 to 1,000 ppm  | 1 ppm      |
| COMBUSTIBLE SENSORS  |                 |            |
| CATALYTIC LEL  | 0 to 100% LEL   | 1% LEL     |
| NDIR (0-100% LEL METHANE)                                    | 0 to 100% LEL   | 1% LEL     |
| NDIR (0-100% VOL. METHANE) <sup>5</sup>                      | 0 to 100% Vol.  | 0.1% Vol.  |
| CARBON DIOXIDE SENSOR  |                 |            |
| CARBON DIOXIDE (CO <sub>2</sub> ) NDIR                       | 0 to 50,000 ppm | 100 ppm    |
| ELECTROCHEMICAL SENSORS                                      |                 |            |
| AMMONIA (NH <sub>3</sub> )                                   | 0 to 100 ppm    | 1 ppm      |
| CARBON MONOXIDE (CO)   | 0 to 500 ppm    | 1 ppm      |
| CARBON MONOXIDE (CO), EXT. RANGE                             | 0 to 2,000 ppm  | 10 ppm     |
| CARBON MONOXIDE (CO), H <sub>2</sub> -COMP.                  | 0 to 2,000 ppm  | 10 ppm     |
| CARBON MONOXIDE (CO) <sup>4</sup>                            | 0 to 500 ppm    | 1 ppm      |
| HYDROGEN SULFIDE (H <sub>2</sub> S) COMBO                    | 0 to 200 ppm    | 0.1 ppm    |
| CHLORINE (CL <sub>2</sub> )                                  | 0 to 50 ppm     | 0.1 ppm    |
| CHLORINE DIOXIDE (CLO <sub>2</sub> )                         | 0 to 1 ppm      | 0.03 ppm   |
| ETHYLENE OXIDE (ETO-A)                                       | 0 to 100 ppm    | 0.5 ppm    |
| ETHYLENE OXIDE (ETO-B)                                       | 0 to 10 ppm     | 0.1 ppm    |
| ETHYLENE OXIDE (ETO-C), EXT. RANGE <sup>9</sup>              | 0 to 500 ppm    | 10 ppm     |
| FORMALDEHYDE (HCHO)  | 0 to 10 ppm     | 0.05 ppm   |
| HYDROGEN (H <sub>2</sub> ) <sup>9</sup>                      | 0 to 1,000 ppm  | 10 ppm     |
| HYDROGEN CYANIDE (HCN)                                       | 0 to 50 ppm     | 0.5 ppm    |
| HYDROGEN SULFIDE (H <sub>2</sub> S)                          | 0 to 100 ppm    | 0.1 ppm    |
| HYDROGEN SULFIDE (H <sub>2</sub> S), EXT. RANGE <sup>9</sup> | 0 to 1,000 ppm  | 1 ppm      |
| METHYL MERCAPTAN (CH <sub>3</sub> -SH)                       | 0 to 10 ppm     | 0.1 ppm    |
| NITRIC OXIDE (NO)  | 0 to 250 ppm    | 0.5 ppm    |
| NITROGEN DIOXIDE (NO <sub>2</sub> )                          | 0 to 20 ppm     | 0.1 ppm    |
| OXYGEN (O <sub>2</sub> )                                     | 0 to 30% Vol.   | 0.1% Vol.  |
| OXYGEN (LIQ O <sub>2</sub> )                                 | 0 to 30% Vol.   | 0.1% Vol.  |
| PHOSPHINE (PH <sub>3</sub> )                                 | 0 to 20 ppm     | 0.1 ppm    |
| PHOSPHINE H (PH <sub>3</sub> H)                              | 0 to 20 ppm     | 0.1 ppm    |
| SULFUR DIOXIDE (SO <sub>2</sub> )                            | 0 to 20 ppm     | 0.1 ppm    |

<sup>1</sup> A two-gas combination sensor is required for a 6-gas configuration.  
<sup>2</sup> Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.  
<sup>3</sup> AutoRAE 2 supports the MultiRAE Lite pumped version only.  
<sup>4</sup> PID sensor requires a pumped configuration.  
<sup>5</sup> NDIR combustible sensors require a pumped configuration in CSA countries.  
<sup>6</sup> RAE Systems recommends calibrating sensors on installation.  
<sup>7</sup> Specifications are subject to change.  
<sup>8</sup> Specification for non-wireless monitors.  
<sup>9</sup> Supported in MultiRAE Lite Diffusion only.  
<sup>10</sup> Please contact RAE Systems for specific wireless approvals

## ORDERING INFORMATION (MODELS: PGM-6208 and PGM-6208D)

- Wireless<sup>2</sup> and non-wireless configurations are available
- Refer to the Portables Pricing Guide for part numbers for monitors, accessories, sampling and calibration kits, gas, sensors, and replacement parts

### For more information

www.honeywellanalytics.com  
www.raesystems.com

### Europe, Middle East, Africa

Life Safety Distribution GmbH  
Tel: 00800 333 222 44 (Freephone number)  
Tel: +41 44 943 4380 (Alternative number)  
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)  
gasdetection@honeywell.com

### Americas

Honeywell Analytics Distribution Inc.  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
detectgas@honeywell.com  
Honeywell RAE Systems  
Phone: +1 408 952 8200  
Toll Free: +1 888 723 4800

### Asia Pacific

Honeywell Analytics Asia Pacific  
Tel: +82 (0) 2 6909 0300  
India Tel: +91 124 4752700  
China Tel: +86 10 5885 8788-3000  
analytics.ap@honeywell.com

### Technical Services

EMEA: HAexpert@honeywell.com  
US: ha.us.service@honeywell.com  
AP: ha.ap.service@honeywell.com

Datasheet\_MultiRAE Lite\_DS-1071-11\_US-EN  
04/18 ©2018 Honeywell International Inc.

Device Management with  
Honeywell SafetySuite



honeywellanalytics.com/SafetySuite

**Honeywell**