



**Product Family**  
**Uvex Genesis S (Slim)**








Wrap-around, uni-lens style for superior coverage. Flexible fingers on nosepiece conform to a variety of nasal profiles. Frame and lens are 6% smaller than Genesis to fit slimmer facial profiles.

[Learn more about all of our Uvex plano products at uvex.us >](http://uvex.us)

[Learn more about our Uvex Rx safety frames at uvexrx.com >](http://uvexrx.com)



**Product Numbers & Ordering Information**

Product Numbers	Details
 S3700	<b>Pewter &amp; Black Frame</b> Clear Lens, Ultra-dura Anti-scratch Coating
 S3700X	<b>Pewter &amp; Black Frame</b> Clear Lens, Uvextreme Anti-fog Coating
 S3700D	<b>Pewter &amp; Black Frame</b> Clear Lens, Dura-streme Dual Anti-fog/Anti-Scratch
 S3701	<b>Pewter &amp; Black Frame</b> Gray Lens, Ultra-dura Anti-scratch Coating
 S3701X	<b>Pewter &amp; Black Frame</b> Gray Lens, Uvextreme Anti-fog Coating
 S3702	<b>Pewter &amp; Black Frame</b> Amber Lens, Ultra-dura Anti-scratch Coating
 S3702X	<b>Pewter &amp; Black Frame</b> Amber Lens, Uvextreme Anti-fog Coating

Uvex Genesis S (Slim)



S3703

**Pewter & Black Frame**  
SCT-Reflect 50 Lens, Ultra-dura Anti-scratch Coating

---



S3704

**Pewter & Black Frame**  
Dark Gray Lens, Ultra-dura Anti-scratch Coating

---



S3720

**Ice Blue Frame**  
Clear Lens, Ultra-dura Anti-scratch Coating

---



S3720X

**Ice Blue Frame**  
Clear Lens, Uvextreme Anti-fog Coating

---



S3720D

**Ice Blue Frame**  
Clear Lens, Dura-streme Dual (Anti-fog/Anti-scratch)

---



S3721

**Ice Blue Frame**  
Gray Lens, Ultra-dura Anti-scratch Coating

---



S3721X

**Ice Blue Frame**  
Gray Lens, Uvextreme Anti-fog Coating

---



S3722

**Ice Blue Frame**  
Amber Lens, Ultra-dura Anti-scratch Coating

---



S3722X

**Ice Blue Frame**  
Amber Lens, Uvextreme Anti-fog Coating

---



S3723

**Ice Blue Frame**  
SCT-Reflect 50 Lens, Ultra-dura Anti-scratch Coating

---



S3724

**Ice Blue Frame**  
Dark Gray Lens, Ultra-dura Anti-scratch Coating

---



S6610

**Replacement Lens**  
Clear, Ultra-dura Anti-scratch Coating

---



S6610X

**Replacement Lens**  
Clear, Uvextreme Anti-fog Coating

---

## Uvex Genesis S (Slim)



S6610D

### Replacement Lens

Clear, Dura-streme Dual (Anti-fog / Anti-scratch) Coating



S6611

### Replacement Lens

Gray, Ultra-dura Anti-scratch Coating



S6611X

### Replacement Lens

Gray, Uvextreme Anti-fog Coating



S6612

### Replacement Lens

Amber, Ultra-dura Anti-scratch Coating



S6612X

### Replacement Lens

Amber, Uvextreme Anti-fog Coating



S6613

### Replacement Lens

SCT-Reflect 50, Ultra-dura Anti-scratch Coating



S6614

### Replacement Lens

Dark Gray, Ultra-dura Anti-scratch Coating

### Packaging Information

Packaging (spectacle) Ind. box, 10/stocker, 200/case Weight (spectacle) 1.125 oz. (31.9g) Ind. Box-Bag Dimensions (spectacle) 6.9 x 2.7" x 2.5" (17.6 x 6.9 x 6.4 cm) " Ind. Box-Bag weight (spectacle) 1.9 oz (54 g) Stocker dimensions (spectacles) 11.8 x 7" x 5.7" (30 x 17.8 x 14.5 cm) " Stocker weight (spectacle) 1.4 lbs (0.65 kg) Master Case Dimensions (Spectacle) 28.9 x 14.5" x 23.6" (73.5 x 36.9 x 60 cm) " Master Case Weight (Spectacle) 31.3 lbs (14.2 kg) Packaging (Repl. Lens) 1 pr./polybag, 10 pr./bag, 200 pr./box Unit Weight (Repl. Lens) 0.05 lb (19.81gm) Ind. Box-Bag dimensions (Repl. Lens) 9 x 5" x 1 7/8" (2.29cm x 12.7cm x 4.76cm) " Ind. Box-Bag weight (Repl. Lens) 0.74 oz. (21g) Stocker dimensions (Repl. Lens) 6 3/4" x 6 3/4" x 2 7/8" (17cm x 17cm x 7cm) Stocker weight (Repl. Lens) 1.10 lbs (.50 kg) Case Dimensions (Repl. Lens) 18.4" x 13.2" x 10" (46.8cm x 33.6cm x 25.4cm) Case Weight (Repl. Lens) 11.03 lb(5kg)

## Overview

### Key Features

The Genesis S (Slim) is the latest addition to the number one selling eyewear family on the market today. Adding to the comfort, performance and style of the Genesis family, the Genesis S (Slim) offers a 6% smaller frame for workers with slimmer facial profiles. Once again, we've made it easier to fit more workers with the best selling safety eyewear in the world. More faces. More choices. More compliance.

- Wrap-around, 9-base uni-lens style for uncompromised peripheral vision and coverage
- Available with Dura-streme dual coating technology which combines our two best lens coatings — Uvextreme anti-fog on the interior and Ultra-dura anti-scratch on the exterior — for 3x longer lens life\*
- Available in Clear, Amber, Gray, Dark Gray, and SCT-Reflect 50 lens tints
- Soft brow guard absorbs and diffuses impact energy
- Soft, flexible "fingers" on nosepiece cMade onform to a variety of facial profiles and minimize slippage
- Padded temple and tips provides all-day comfort
- Economical and easy lens replacement system allows for multiple lens tints and extends the life of the eyewear
- Multiple models in a family offers standardization while offering workers choice
- Lifetime frame guarantee
- Made in USA

**Recommended Industries/Use**

- Construction
- Food Services
- Pharmaceutical

**Hazards**

- Abrasion
- Airborne Particulates
- Biohazard
- Impact
- Low Visibility

**Regulations**

- ANSI Z87+ (High Impact) - Meets ANSI Z87+ (High Impact)
- ANSI Z 87.1/1989, CA 18,819 - Meets ANSI Z 87.1/1989, CA 18,819 ([http://www.mte.gov.br/Empregador/segsau/Pesquisa/CA\\_DET.asp?vNRCAProc=18819&Equipamento=00&NOEquipamento=&Fabricante=00&NOFabricante=](http://www.mte.gov.br/Empregador/segsau/Pesquisa/CA_DET.asp?vNRCAProc=18819&Equipamento=00&NOEquipamento=&Fabricante=00&NOFabricante=))
- CSA Z94.3 - Tested by Honeywell to meet the requirements of the CSA Z94.3 standard
- Military V0 - Meets military V0 ballistic test for impact

**Historical Brand**

Uvex

**Warranty Information**

Lifetime frame guarantee

**Specifications**

**Lens overall width**

- 5.35" (136 mm) nominal

**Lens material**

- Polycarbonate

**Lens coating**

- Ultra-dura<sup>®</sup>, Anti-Scratch Coating, Uvextreme<sup>®</sup> AF Anti-Fog Coating, Dura-Streme Technology (Dual Anti-Fog & Anti-Scratch) Coating "

**Lens thickness**

- 0.067" (1.7 mm) minimum

**Lens tints**

- Clear, Amber, Gray, Dark Gray, SCT-Reflect 50

**Lens base curve**

- 9 Base

**Replacement lenses or foam available**

- Yes

**Rx capable**

- No

**Temple material**

- Polycarbonate with elastomer

**Temple length**

- 4.25" (105 mm) actual, 5.51" (140 mm) fit

**Temple set-back**

- 3.1" (79 mm)

**Temple style**

- Spatula (one piece) with elastomer padding

**Frame material**

- Polycarbonate with elastomer

**Frame colors**

- Pewter/Black, Ice Blue /Gray

**Dielectric frame**

- Yes

## Certifications

### ANSI Certificate of Compliance\_Eng

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Laser\\_Filters\\_\\_\\_Eyewear/19294/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Laser_Filters___Eyewear/19294/1033.aspx)

ANSI Certificate of Compliance\_Eng

### ANSI Certificate of Compliance\_Spanish

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Laser\\_Filters\\_\\_\\_Eyewear/19295/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Laser_Filters___Eyewear/19295/1033.aspx)

ANSI Certificate of Compliance\_Spanish

## Literature & Documents

### Data Sheet Eyewear Uvex Genesis Slim-Eng

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Eyewear/19053/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Eyewear/19053/1033.aspx)

Data Sheet Eyewear Uvex Genesis Slim-Eng

### Data Sheet Eyewear Uvex Genesis Family Broucher-Eng

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Eye\\_and\\_Face\\_Protection/Eyewear/19055/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Eye_and_Face_Protection/Eyewear/19055/1033.aspx)

Data Sheet Eyewear Uvex Genesis Family Broucher-Eng

## Training & Proper Use

All products come packaged with instructions and warnings for proper use.

## Technical Support

(800) 682-0839, Sperian Protection Americas, Customer Care