



Miller DuraSeal™ Self-Retracting Lifeline

Designed to lower your cost of ownership
by keeping it in the field



- Prevents contaminants from entering the unit with highest industry rated sealed technology IP69K
- Built to last reusable brake design withstands multiple falls
- Quick, low cost repair is achieved with field replaceable lifeline
- Reduces fatigue and increases productivity with units up to 30% lighter than competitive sealed units
- Product service life is extended in the harshest environments with corrosion resistant components

Honeywell | Fall Protection

Honeywell Miller DuraSeal™ Self-Retracting Lifeline

The new patent-pending Miller DuraSeal™ Self-Retracting Lifeline (SRL) is designed to perform in the harshest environments including onshore and offshore oil and gas, mining and petrochemical. The sealed technology, reusable brake system, field replaceable lifeline and corrosion resistant materials keep the product in the field to lower your cost of ownership.



Miller DuraSeal™ Competitive Advantages

Prevents contaminants from entering the unit with highest industry rated sealed technology IP69K

In addition to meeting IP68, the Miller DuraSeal™ meets IP69K – a more stringent test requiring close range high-pressure/high temperature spray downs. The Miller DuraSeal design entirely seals and protects the brake system, power spring and bearings to ensure these components are never exposed to debris, water or chemicals.

System built to last, withstanding multiple falls

The robust brake design withstands multiple falls, keeping the Miller DuraSeal™ in the field, lowering your cost of ownership.

Provides quick, low-cost repair

The Miller Rapid Replace field replaceable lifeline can be performed by the end-user in the field or an authorized Miller Repair Center.

Provides easier installation and transport

The lightest weight sealed SRL offering includes models up to 30% lighter than competitive sealed SRLs for easier installation and transport.

Enables quicker, easier installation and provides protection from rain

Models with mounting plate for attachment to a 4-hole bolt pattern common on oil and gas rigs include built-in spacers for easier installation. Waterproof design protects cable from rain.

Provides protection for a wider range of workers

The 420 lb. (189 kg) weight capacity provides protection for a wider range of workers carrying heavy tools.

Increases service life with new spring design

The power spring design keeps tension on the line, increasing the life service of the unit.

Prevents brake disengagement during a fall

Anti-ratcheting brake design provides positive brake engagement.

Lowers cost of ownership with no annual factory recertification

The robust design does not require annual recertification.* This keeps the product in the field lowering cost of ownership and increasing productivity.

*Except in Canada where the Canadian Standards Association require annual recertification.




Rotating Anchor Loop

Balances the unit to ensure the load is centered in the event of a fall.

Mounting Plate with Integral Spacers*

Integral spacers provide quicker, easier installation. A gasket between the housing and mounting plate prevents rain from entering the cable side of the unit.

*Applies to models with mounting plates only



Aluminum and Stainless Housing

Designed with corrosion resistant components, the Miller DuraSeal provides ultimate durability extending the product's service life.

Ergonomically Designed Carrying Handle/Secondary Anchorage

Provides a comfortable well-balanced feel and is approved for use as a secondary anchorage attaching the SRL to the structure using a tether line.

Miller Rapid Replace Lifeline

The field replaceable lifeline provides for quick, low-cost repair that can be performed by the end-user in the field or an authorized Miller Repair Center.

Equipped with Ultra-high Frequency RFID

Enables asset and inspection tracking.

Lifeline Grip

Optimized to provide a solid grasp of the lifeline when connecting to the user's harness.

Swivel

Built-in swivel prevents the lifeline from twisting.

Load Indicator

Activates in the event of a fall.

3,600 lb. Gate

The 3,600 lb. gate-strength hooks meet the most recent industry standards.

Field Replaceable Lifeline

The Miller Rapid Replace Line provides for quick, low-cost repair that can be performed by users in the field or an authorized Miller Repair Center.


For full step-by-step instructions, visit millerfallprotection.com



Pull out the entire length of cable until shoulder screws are visible and activate lock.



Remove the two shoulder screws on the drum through the side plate cover.



Insert new lifeline into the unit, install shoulder screws and ensure it has engaged.

Honeywell Miller DuraSeal™ Self-Retracting Lifeline

Designed to lower your cost of ownership by keeping it in the field

	SKU	LENGTH	LIFELINE MATERIAL	WEIGHT	DIMENSIONS		
					LENGTH	WIDTH	DEPTH
 ATTACHING WITH CARABINER	Miller DuraSeal™ Sealed SRL with cable sling, tagline and 2 carabiners						
	SSRL50G1	50-ft (15 m)	Galvanized Steel	27.3 lb. (12 kg)	12.8 in. (325 mm)	11.8 in. (300 mm)	4.9 in. (125 mm)
	SSRL50S1	50-ft (15 m)	Stainless Steel	27.3 lb. (12 kg)	12.8 in. (325 mm)	11.8 in. (300 mm)	4.9 in. (125 mm)
	SSRL100G1	100-ft (30 m)	Galvanized Steel	59.7 lb. (27 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL100S1	100-ft (30 m)	Stainless Steel	59.7 lb. (27 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL130G1	130-ft (40 m)	Galvanized Steel	61.7 lb. (28 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL130S1	130-ft (40 m)	Stainless Steel	61.7 lb. (28 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL175G1	175-ft (53 m)	Galvanized Steel	76.5 lb. (35 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	7.8 in. (198 mm)
SSRL175S1	175-ft (53 m)	Stainless Steel	76.5 lb. (35 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	7.8 in. (198 mm)	
 ATTACHING WITH 4-BOLT HOLE PATTERN	Miller DuraSeal™ Sealed SRL with cable sling, tagline, 2 carabiners and 4-hole mounting plate						
	SSRL100G2	100-ft (30 m)	Galvanized Steel	61 lb. (28 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL100S2	100-ft (30 m)	Stainless Steel	61 lb. (28 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL130G2	130-ft (40 m)	Galvanized Steel	63 lb. (29 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL130S2	130-ft (40 m)	Stainless Steel	63 lb. (29 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	6.6 in. (168 mm)
	SSRL175G2	175-ft (53 m)	Galvanized Steel	77.9 lb. (29 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	7.8 in. (198 mm)
	SSRL175S2	175-ft (53 m)	Stainless Steel	77.9 lb. (29 kg)	15.7 in. (399 mm)	14.4 in. (366 mm)	7.8 in. (198 mm)

Ensure your worker's safety with a full range of Honeywell Oil and Gas products!



Uvex Livewire™
with Hydroshield™



Miller AirCore™ Oil
and Gas Harness



Fibre-Metal® P1
Hard Hat



NorthFlex FRGrip™
Plus 5



Oliver® Boots

Visit honeywellsafety.com/USA/OilandGas/ for more information

Limitless Possibilities. Ask the Expert.

www.millerfallprotection.com

Technical Service: 800.873.5242

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI 02917

US
Tel: 800.430.5490
Fax: 800.322.1330

CANADA
Tel: 888.212.7233
Fax: 888.667.8477

www.honeywell.com

LMDSB | Rev 1 | 3/16
© 2016 Honeywell International Inc.

Honeywell