



Material Product Datasheet

TMX3202 ThermaMAX Resin Ribbon

RIBBON CONSTRUCTION

Total Ribbon Thickness (µm)	6.2
Base Film Thickness (µm)	4.5
Ribbon Film Type	Polyethylene Terephthalate

PROPERTIES

Ink Color	Black
Ink Pigment	Carbon Black

INK MELTING POINT (°F)

230

PRINTING

Print Speed (format & material dependent)	6 ips
-------------------------------------------	-------

ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	20	to	85
Shelf Life (months)	12		

CONFORMANCE & CERTIFICATION

FDA Indirect Food Contact	
CONEG Heavy Metals Legislation	✓
UL	✓
cUL	✓
CSA	✓

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Printed on:
8/21/2019

Honeywell Productivity Products - Printer Supplies

9290 LeSaint Drive
Fairfield, Ohio 45014
800-755-5505 opt 2