



## Material Product Datasheet

### TMX2200 ThermaMAX Wax/Resin Ribbon

#### RIBBON CONSTRUCTION

Total Ribbon Thickness ( $\mu\text{m}$ )	8.1
Base Film Thickness ( $\mu\text{m}$ )	4.8
Ribbon Film Type	Polyethylene Terephthalate

#### PROPERTIES

Ink Color	Black
Ink Pigment	Carbon Black

#### INK MELTING POINT (°F)

250

#### PRINTING

Print Speed (format & material dependent)	10 ips
---	--------

#### ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		

#### CONFORMANCE & CERTIFICATION

FDA Indirect Food Contact	
CONEG Heavy Metals Legislation	✓
UL	✓
cUL	
CSA	

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Printed on:  
8/21/2019

**Honeywell Productivity Products - Printer Supplies**

9290 LeSaint Drive  
Fairfield, Ohio 45014  
800-755-5505 opt 2