

UNAMP,4-COND,5-COND,6-COND,4-PIN,5-PIN,6-PIN


| 4-PIN | | 5-PIN | | 6-PIN | |
|-------|----------|-------|-----------|-------|-----------|
| PIN | FUNCTION | PIN | FUNCTION | PIN | FUNCTION |
| A | (+)EXC. | A | (+)EXC. | A | (+)EXC. |
| B | (+)SIG. | B | (+)SIG. | B | (+)SIG. |
| C | (-)SIG. | C | (-)SIG. | C | (-)SIG. |
| D | (-)EXC. | D | (-)EXC./ | D | (-)EXC. |
| | | | TEDS GND | E | TEDS GND |
| | | E | TEDS DATA | F | TEDS DATA |

* USE TEDS CONNECTIONS WHEN REQUIRED

001-LWR-100

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

| | | | | | | |
|---|--------------|--|---|------------------------------|-------------|--------|
| UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS | | A 7/18/2006 | PIN E WAS "TEDS DATA", PIN F WAS "TEDS GND" FOR 6 PIN CONN | MGJ | RJG | MGF |
| AUTOCAD | | - | INITIAL RELEASE TO PRODUCTION | | | |
| REV | DO NOT SCALE | REV | DESCRIPTION | REV BY | CHK BY | APV BY |
| HIST | .X | DRW: DURKIN | CHK: VICARS | MFG: - | ENG: OSMITH | |
| PCB DWG & REV: | ±.1 | 12/15/05 | 05/09/2006 | - | 05/03/2006 | |
| CHECKOUT PROCED: | .XX |  HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing | | | | |
| SCHEMATIC: | ±.01 | | | | | |
| LAYOUT: | .XXX | EXTERNAL WIRING CODE | | UNAMP, 5 & 6-COND, 5 & 6-PIN | | 100 |
| DRILL PATTERN: | ±.005 | CODE IDENT NO. 51518 | DOCUMENT NUMBER | | | |
| | ±1/2" | SHEET 1 OF 1 | SIZE A | 001-LWR-100 | | |