



* KEEP AREA INDICATED
FREE OF METAL PARTS
SEE NOTES 4, 5

- NOTES:
1. SENSOR IS NOT DYNAMICALLY BALANCED.
 2. PILOT DIAMETERS IN ACCORDANCE WITH ANSI B4.1 (ANSI STANDARD FOR LIMITS AND FITS).
 3. MAXIMUM COMPONENT DIAMETER MATING DRIVELINE COMPONENTS MUST NOT EXCEED THIS DIAMETER WITHIN 1.50 INCH OF THE ROTATING ANTENNA.
 4. MINIMUM SAFETY SHIELD CLEARANCE A MINIMUM OF 1.50 INCH MUST BE PROVIDED BETWEEN THE ROTATING ANTENNA AND TEST STAND SAFETY SHIELDS.
 5. SIGNAL LOSS WARNING SIGNAL LOSS WILL OCCUR IF MAXIMUM COMPONENT DIAMETER -OR- MINIMUM SAFETY SHIELD CLEARANCE IS NOT OBSERVED WITHIN 1.50 INCH OF THE ROTATING ANTENNA.

DESIGN UNITS: INCH TOLERANCES UNLESS NOTED:	DRAWN VSY 12 MAY 11 CHECK MAX 12 MAY 11	Honeywell	
NO PLACES .x ± 0.400 ONE PLACE .x ± 0.2 TWO PLACE .xx ± 0.02 THREE PLACE .xxx ± 0.010 ANGLES X ± 0.5°	THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		TITLE OD DRAWING MODEL 92514
THIRD ANGLE PROJECTION	INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY	SIZE D TYPE E CAGE CODE 51518	DRAWING NAME 000-LW92514
	AUTOCAD	SCALE NTS	SHEET 1 OF 1