


UNAMPLIFIED
5-COND, 5-PIN

PIN	DESIGNATION
A	(-)OUTPUT
B	(+)EXCITATION
C	(-)EXCITATION/ TEDS GND
D	(+)OUTPUT
E	TEDS DATA

001-LWR-136

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS		-		INITIAL RELEASE TO PRODUCTION			-	-	-
		REV	DESCRIPTION			REV BY	CHK BY	APV BY	
AUTOCAD		DRW: FOWLER	CHK: -	MFG: -	ENG: OSMITH				
		05/19/2006	-	-	05/22/2006				
REV HIST	DO NOT SCALE	 HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing							
	.X								
	.XX								
	.XXX								
	±.2	EXTERNAL WIRING CODE							
	±.02								
	±.010	SPECIAL, 5-COND, 5-PIN							
		CODE IDENT NO. 51518			DOCUMENT NUMBER				
		SHEET 1 OF 1		SIZE A		001-LWR-136			