

Systevo control center (230 VAC)



Features:

- Mini control center
- Mainboard with Quad-Core µP J19xx, 2 GHz or equivalent, min. 4 GB RAM
- 1* Solid-State HDD (SSD) min. 128 GB
- Power supply: 230 V AC
- 3* RS232, 1* parallel, USB, VGA/HDMI
- 2* LAN Ethernet (min. 10/100 MBit)
- Hardened operating system Windows 10 IoT Entry
- Software for configuration
- Software for Systevo Call Ackermann
- Continuous operation: 24/7

Part-No.: 72662C

Control center for the configuration, display, operation and logging for Systevo Call Ackermann, equipped with system release V11, incl. the system license of the operation of max. 200 rooms. Additional system licenses required depending on the system functions/size. Optionally as an interface to third-party systems, such as DECT system, fire detection system. Comprised of a high-quality system processor with SSD and interfaces (RS232, USB, LAN).

Equipping of the user software with system release V11:

Configuration tool Systevo Call Ackermann Allocation to room configuration (license: max. 200 room) Definition of functions/parameters of the call system in accordance with DIN VDE 0834-1: 2016-06 Set-up of the call types, call type groups, call type upgrades Set-up of the VoIP/SIP channel for mobile call querying via DECT/WIFI (separate license/SIP license required) Configuration of input/output events for controlling external systems: Light/blind/TV Setting of radio and TV channel System management tools, database management system Network functions for system accesses Freely configurable services (interconnection) Allocation of timed services Selection of call type groups for services Configuration of the volume of the acoustic call forwarding (day/night) Definition of target-oriented forwarding between stations (call types) Freely configurable announcement functions Selection of destinations for announcements Fault monitoring and reporting (in accordance with DIN VDE 0834-1: 2016-06) Access control via user ID (if required) Output of the data on a printer

Optional:

Message transmission to a wireless messaging system (e.g. WIFI-/DECT system) Freely configurable recipient addresses for messages from groups of the call system Definition of the display format for the messages to be transmitted Set-up of various services (e.g. day, night service) Allocation of repetition times, acoustic call tones, etc.

Rated voltage	230 V AC
Ambient temperature	10 °C ... 35 °C
Storage temperature	0 °C ... 50 °C
Air humidity	< 20 %
Weight	approx. 3,2 kg
Dimensions	W: 254 mm H: 88 mm D: 220 mm



EN 55022/55024/61000-3/60950-1 2004/108/EC, 2006/95/EC, 2005/32/EC 2003/95/EC, Regulation (EC) 1275/2008 Product not available anymore. We recommend using the Systevo Workstation 765M440 with System-Release 12.