

Systevo Touch IP Management Server for Edt. 25 users



Part-No.: 79CM305SR

Management server for the configuration, administration and logical room allocation of the touch terminals. Provision of the web services for the entire system infrastructure to Systevo Call Ackermann. Interface via LAN infrastructure to the system workstation (FTP/NTS/HTML). Provision of a secure system environment (Cyber Security conform) for automated firmware updates of the touch terminals.

Features:

- BCM2837, 1.2 GHz, Quad-Core
- RAM 1 GByte
- Flash memory 4 GByte
- ESD protection 4 kV / 8 kV
- 3 Status LEDs (2-coloured), of which, 2 LEDs freely programmable
- Operating system
- Raspbian - Version Jessie with RT-Patch (Installation)
- 2 x USB 2.0 A (per 500 mA resilient) | 1 x Micro-USB |
- 1 x Micro HDMI | 1 x RJ45 (Ethernet) 10/100 Mbit/s
- Configuration tool Systevo Touch IP (max. 25 devices)
- Processing of the XML configuration data of the Systevo Call Ackermann
- Logical allocation of the touch terminals to the rooms (patient rooms, offices), incl. visualisation
- Allocation of the system language
- Allocation of time-dependent comfort functions (day and night mode)
- Configuration of graphic display elements (logo, background colour)
- Set-up of the SIP channel for communication via VoIP (sep. licence/SIP licence required)
- System management tools
- Fallback level for DNS, DHCP
- Database management system
- Network functions for system accesses (VNC SSH-Tunnel via certificate for operating system and application)
- Firmware updates of the touch terminals
- Selection of call type groups for services
- Configuration of the level of the acoustic call forwarding (day/night)
- Access control via user ID (if necessary)

Operating voltage	10,7 ... 28,8 V DC
Power consumption	10 W (incl. USB load relay with 2 x 450 mA)
Ambient temperature	-40 °C ... 55 °C (exceeds requirements of EN 61131-2)
Storage temperature	-40 °C ... 85 °C
Air humidity	< 93 %
Type of protection	IP 20
Weight	approx. 108 g
Dimensions	W: 22.5 mm H: 96 mm D: 110,5 mm



Product not available anymore. Valid for System V11 only.