

Duty room interface (4 lamps), white




Part-No.: 72583A1


Office interface with integrated signal lamp, designed with four lamp chambers in electricity-saving LED technology. Serves as a controller for offices with voice function, in order to integrate the concentrated station query (CSQ) into the room bus. With integrated switching technology for passive call and cancellation units incl. call group monitoring, the input and output parameters are adaptable to the local requirements. Local storage of the configuration data, including the 8-digit alphanumeric text for the office, display and audio parameters, special functions and additional display texts (call types etc.). Equipped with service socket for the configuration module and selector switch for standby current/operating current. Support with commissioning due to remote access functions. Easy assembly due to service-friendly joining technology in conjunction with related connection board. Integration into the room terminal interface in the room bus. Upgradable to future system firmware due to forward-looking flash technology. Room bus for digital data and audio transmission. Interface for connecting a concentrated station query. Configuration socket for optional decentralised configuration in conjunction with the configuration module. Service socket for the connection of analysis tools. Standby current/operating current option. Compatibility mode for DIN VDE 0834: 1991 | from 2000 Service and remote access functions. Signal lamp that can be switched off (in conjunction with blind plate)

Features:

- Room calls: Normal call, emergency call, diagnostic call, doctor call
- Cancellation and presence: Combined cancellation/presence, Presence 1 (green)
- Acoustic signals: Call transfer for normal call and emergency call, doctor call, staff call, meal call
- Control of optical signals: WC call lamp (white), room call lamp (red), AW (cancellation and presence) lamps (green and yellow)
- Security function: Short-circuit resilient, call circuit monitoring

Material	housing: PB + ABS - FR
Color	white, similar to RAL 9016
Weight	approx. 225 g
Dimensions	W: 158 mm H: 110 mm D: 90,5 mm

 Product not available anymore. Additional information see 74422A1N

 including dummy cover plate

Accessories:

72583Z1	Connection board for the service room interface, white
73070A	Databus connection unit for master station
74422A1N	Master station