

Basic Systevo DECT central unit




Part-No.: 790D15B


Central unit, optimised for small to medium-sized facilities, as basic housing for the telecommunication system according to the DECT/GAP standard for upgrading a telephone system with analogue extension participants and/or VoIP participants. Already fitted with a CPU card (without link communication interface) and 1 plug-in card for the administration of up to 8 DECT base stations. The modular system upgrade of the central unit in accordance with the customer requirements with 2 additional plug-in cards for the administration of the DECT base stations and extension users (a/b and VoIP/SIP). Up to 150 DECT telephones can be administered from the Basic Systevo DECT central unit.

Features:

- 1 small center housing with Backplane
- 1 Power supply unit for the supply of the plug-in cards
- Max. installation of 1 CPU-card and 3 further plug-in cards
- TBR6(DECT RF), TBR22(GAP), EMC ETS300329, CE

Frequency range	1880 MHz ... 1900 MHz
Ambient temperature	-10 °C ... 40 °C
Air humidity	< 20 %
Mounting	Station housing
Weight	approx. 1,16 kg (without power supply)
Dimensions	W: 194 mm H: 177 mm D: 330 mm

 Product available until June 2021

 Basic Systevo DECT central unit System documentation System software for set-up and configuration

Accessories:

790D001 Connection cable 5 m PC